# Pivot pin
# CRZNG-50

Part number: 161854



General operating condition

## Data sheet

| Feature | Value |
|---|---|
| Size | 50 |
| Based on norm | ISO 15552 |
| Corrosion resistance class (CRC) | 4 - Particularly high corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Suitability for the production of Li-ion batteries | Metals with more than 5% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils |
| Ambient temperature | -40 °C ... 150 °C |
| Product weight | 473 g |
| Note on materials | RoHS-compliant |
| Mounting material | High-alloy stainless steel |
| Material of screws | High-alloy stainless steel |

# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## FESTO:

NPQP-Y-Q6-E-FD-P10 NPQP-T-Q8-E-FD-P10 QS-1/2-16 QS-1/8-8-I QSLL-G1/2-12 VBQF-U-G14-E 153367 QSML-6 NPQP-Y-R12-Q12-FD QS-10H-6 153151 153269 NPQP-LQ-R18-Q4-FD-P10 VABM-B10-25S-G38-6-P3 153031 NPQH-T-Q14-E-P10 NPQP-L-Q10-E-FD-P10 QSS-8-F SASC-P4-A-M8-A SGS-M10X1,25 VABM-B10-25S-G38-10 CRVZS-0.4 DSBC-80-20-D3-PPSA-N3 QSF-3/8-8-B QSF-1/4-8-B QSY-6H-4 153307 HGL-1/8-QS-6 NPQP-D-Q4-S8-FD-P10 NPQP-LQ-R18-Q8-FD-P10