
Pivot pin kit
DAMT-V1-40-A

Part number: 2214899



General operating condition

Data sheet

Feature	Value
Size	40
Based on norm	ISO 15552 (previously also VDMA 24562, ISO 6431, NF E49 003.1, UNI 10290)
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Suitability for the production of Li-ion batteries	Metals with more than 1% by mass of copper are excluded from use. Exception are printed circuit boards, cables, electrical connectors and coils
Ambient temperature	-40 °C ... 150 °C
Product weight	387.5 g
Note on materials	RoHS-compliant
Material of screws	Steel Galvanized
Trunnion flange material	Steel, galvanized
Clamping piece material	Steel, galvanized
Rod material	High-alloy stainless steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

HGL-1/8-QS-6 NPQP-D-Q4-S8-FD-P10 QS-10H-6 QSLL-G1/2-12 153031 153367 NPQH-T-Q14-E-P10 QSML-6 VABM-B10-25S-G38-10 153151 153269 QSF-3/8-8-B QSY-6H-4 SASC-P4-A-M8-A CRVZS-0.4 DSBC-80-20-D3-PPSA-N3 QSS-8-F VABM-B10-25S-G38-6-P3 VBQF-U-G14-E 153307 NPQP-L-Q10-E-FD-P10 NPQP-Y-R12-Q12-FD SGS-M10X1,25 NPQP-LQ-R18-Q8-FD-P10 NPQP-T-Q8-E-FD-P10 QS-1/8-8-I NPQP-LQ-R18-Q4-FD-P10 QS-1/2-16 QSF-1/4-8-B NPQP-Y-Q6-E-FD-P10