






## SPECIFICATIONS

Current Rating: 1.0 Amps
Withstanding Voltage: AC 500V
Insulation Resistance: 1000MΩ Min
Contact Resistance: 20mΩ Max
Operation Temperature: -40° to+105°
Insrlator Material: Polyester(UL94V-0)
Contact Material: Brass
Standard: PA6T
Contact Plating: Gold Flash
Max.Processing Temp: 240° C for30-60seconds
(260° C for5seconds)




RECOMMEND P.C.B LAYOUT
PCB TOLERANCE: ±0.05 (TOP VIEW)

深圳市韩下电子有限公司

| | | | | | |
|---|---|---|---|---|---|
| UNLESS OTHEWIXE SPECIFIED TOLERANCE<br>X :±0.30 X° :±5°<br>X.X :±0.25 X.X° :±1°<br>X.XX:±0.20 X.XX° :±0.5° | DRAWM NAME: | HX PZ1.27-2x4P TP | | | |
| | SIZE | A4 | SCALE | N:1 | PROUCT NO. |
| | REV | A | UNIT | mm | PROJECT |
| | | | | | PAGE 1/1 |
| DRAWN: 黄彬 2020.6.24 | CHECKED: 张伟 2020.6.24 | | APPROVED: 罗小春 2020.6.24 | | |

| No.of | DIM.A | DIM.B | No. of | DIM.A | DIM.B | No. of | DIM.A | DIM.B | No. of | DIM.A | DIM.B | No. of | DIM.A | DIM.B |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | — | — | 11 | 12.70 | 13.97 | 21 | 25.40 | 26.67 | 31 | 38.10 | 39.37 | 41 | 50.80 | 52.07 |
| 2 | 1.27 | 2.54 | 12 | 13.97 | 15.24 | 22 | 26.67 | 27.94 | 32 | 39.37 | 40.64 | 42 | 52.07 | 53.34 |
| 3 | 2.54 | 3.81 | 13 | 15.24 | 16.51 | 23 | 27.94 | 29.21 | 33 | 40.64 | 41.91 | 43 | 53.34 | 54.61 |
| 4 | 3.81 | 5.08 | 14 | 16.51 | 17.78 | 24 | 29.21 | 30.48 | 34 | 41.91 | 43.18 | 44 | 54.61 | 55.88 |
| 5 | 5.08 | 6.35 | 15 | 17.78 | 19.05 | 25 | 30.48 | 31.75 | 35 | 43.18 | 44.45 | 45 | 55.88 | 57.15 |
| 6 | 6.35 | 7.62 | 16 | 19.05 | 20.32 | 26 | 31.75 | 33.02 | 36 | 44.45 | 45.72 | 46 | 57.15 | 58.42 |
| 7 | 7.62 | 8.89 | 17 | 20.32 | 21.59 | 27 | 33.02 | 34.29 | 37 | 45.72 | 46.99 | 47 | 58.42 | 59.69 |
| 8 | 8.89 | 10.16 | 18 | 21.59 | 22.86 | 28 | 34.29 | 35.56 | 38 | 46.99 | 48.26 | 48 | 59.69 | 60.96 |
| 9 | 10.16 | 11.43 | 19 | 22.86 | 24.13 | 29 | 35.56 | 36.83 | 39 | 48.26 | 49.53 | 49 | 60.96 | 62.23 |
| 10 | 11.43 | 12.70 | 20 | 24.13 | 25.40 | 30 | 36.83 | 38.10 | 40 | 49.53 | 50.80 | 50 | 62.23 | 63.50 |

深圳市韩下电子有限公司
Shenzhen Hanxia Electronic Co., Ltd
Tel: 0755-23086569

# 承　认　书

# SPECIFICATION FOR APPROVAL

**产 品 编 码**
**Material code:** _____

产品名称 Project：排针

规格型号 Part No：HX PZ1.27-2x4P TP

**贵公司承认印 Approal slgnatures**

| 料 号/Part No. | 签　章/Signatures |
|---|---|
| | |

日期 Date:

| | | |
|---|---|---|
| 拟制/Drawn | 黄彬 | 深圳市韩下电子有限公司 工程专用章 |
| 审核/Check | 张伟 | |
| 批准/Approved | 罗小春 | |

深圳市韩下电子有限公司