Guided drive
DFM-25-125-B-PPV-A-GF

Part number: 8161428



General operating condition

Data sheet

Feature	Value
Stroke	125 mm
Piston diameter	25 mm
Drive unit operating mode	Yoke
Cushioning	Pneumatic cushioning, adjustable at both ends
Mounting position	Any
Guide	Sliding guide
Structural design	Guide
Position sensing	For proximity sensor
Operating pressure	0.15 MPa ... 1 MPa
Operating pressure	1.5 bar ... 10 bar
Mode of operation	Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Cleanroom class	Class 7 according to ISO 14644-1
Ambient temperature	-20 °C ... 80 °C
Impact energy in the end positions	0.3 J
Theoretical force at 6 bar, retracting	247 N
Theoretical force at 6 bar, advancing	295 N
Alternative connections	See product drawing
Pneumatic connection	G1/8
Note on materials	RoHS-compliant
Cover material	Wrought aluminum alloy
Seals material	NBR
Housing material	Wrought aluminum alloy
Piston rod material	High-alloy stainless steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

VABM-B10-25S-G38-10 NPQP-D-Q4-S8-FD-P10 NPQP-LQ-R18-Q4-FD-P10 NPQP-T-Q8-E-FD-P10 153307 CRVZS-0.4 QS-1/8-8-I QSS-8-F SASC-P4-A-M8-A 153367 NPQP-L-Q10-E-FD-P10 153031 DSBC-80-20-D3-PPSA-N3 HGL-1/8-QS-6 NPQP-Y-R12-Q12-FD QS-10H-6 NPQP-LQ-R18-Q8-FD-P10 NPQP-Y-Q6-E-FD-P10 QS-1/2-16 153151 153269 NPQH-T-Q14-E-P10 VABM-B10-25S-G38-6-P3 QSF-3/8-8-B QSY-6H-4 SGS-M10X1,25 VBQF-U-G14-E QSF-1/4-8-B QSLL-G1/2-12 QSML-6