CMSL130N85A

85V, 3.8mΩ typ., 180A N-Channel MOSFET

General Description

The CMSL130N85A uses advanced SGT technology to provide excellent RDS(ON).It can be used in a wide variety of applications.

Product Summary

BVDSS	$R_{DS(on)}$ max.	ID
85V	4.3mΩ	180A


Applications


- Motor
- BMS
- Load switch

Features

- Low On-Resistance
- 100% avalanche tested
- Surface Mount Package
- RoHS Compliant

TOLL-8 Pin Configuration





TOLL-8
CMSL130N85A

Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	85	V
V_{GS}	Gate-Source Voltage	±20	V
I_D@T_C=25℃	Continuous Drain Current	180	A
I_D@T_C=100℃	Continuous Drain Current	126	A
I_{DM}	Pulsed Drain Current	720	A
EAS	Single Pulse Avalanche Energy[1]	1440	mJ
P_D@T_C=25℃	Total Power Dissipation	300	W
T_{STG}	Storage Temperature Range	-55 to 150	℃
T_J	Operating Junction Temperature Range	-55 to 150	℃

Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction-ambient	---	62	℃/W
$R_{\theta JC}$	Thermal Resistance Junction-case	---	0.42	℃/W

Electrical Characteristics (T_J=25℃ , unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V , I_D=250uA	85	---	---	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V , I_D=50A	---	3.8	4.3	mΩ
$V_{GS(th)}$	Gate Threshold Voltage	V_{GS}=V_{DS} , I_D =250uA	2.0	---	4.0	V
I_{DSS}	Drain-Source Leakage Current	V_{DS}=85V , V_{GS} =0V	---	---	1	uA
I_{GSS}	Gate-Source Leakage Current	V_{GS} =±20V , V_{DS}=0V	---	---	±100	nA
gfs	Forward Transconductance	V_{DS}=10V , I_D=20A	---	65	---	S
R_g	Gate Resistance	V_{DS}=0V , V_{GS}=0V , f=1MHz	---	3.0	---	Ω
Q_g	Total Gate Charge	I_D=50A V_{DS}=40V V_{GS}=10V	---	55	---	nC
Q_{gs}	Gate-Source Charge		---	15	---	
Q_{gd}	Gate-Drain Charge		---	13	---	
$T_{d(on)}$	Turn-On Delay Time	V_{DD} =40V V_{GS} = 10V R_{G_ext} = 3Ω	---	20	---	ns
T_r	Rise Time		---	39	---	
$T_{d(off)}$	Turn-Off Delay Time		---	45	---	
T_f	Fall Time		---	23	---	
C_{iss}	Input Capacitance	V_{DS}=25V , V_{GS}=0V , f=1MHz	---	4150	---	pF
C_{oss}	Output Capacitance		---	1800	---	
C_{rss}	Reverse Transfer Capacitance		---	120	---	

Diode Characteristics


Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_S	Continuous Source Current	V_G=V_D=0V , Force Current	---	---	180	A
I_{SM}	Pulsed Source Current		---	---	720	A
V_{SD}	Diode Forward Voltage	V_{GS}=0V , I_S=50A	---	0.86	1.4	V
t_{rr}	Reverse Recovery Time	I_S =20A di/dt =500A/μs	---	60	---	ns
Q_{rr}	Reverse Recovery Charge		---	560	---	nC

Note :


1.The EAS data shows Max. rating . The test condition is V_{DD}=50V , V_{GS}=10V , L=5mH , I_{AS}=24A.

This product has been designed and qualified for the counsumer market.
Cmos assumes no liability for customers' product design or applications.
Cmos reserver the right to improve product design ,functions and reliability wihtout notice.Please refer to the latest version of specification.


Typical Characteristics




Output Characteristics




transfer characteristics




drain-source on-resistance



Gate charge vs gate-source voltage




Capacitance Characteristics





Body-Diode Characteristics

Package Dimension

TOLL-8 Unit :mm







SYMBOL		A	b	b1	b2	b3	b4	b5	b6	c	D	D1	D2	D3	D4	D5	e	E	E1
MILLIMETER	MIN.	2.2	0.7	9.7	0.36	0.05	0.3	1.1	3	0.4	10.28	10.98	3.2	7.15	3.59	3.26	1.1	9.8	7.4
	TYP.	2.3	0.8	9.8	0.45	0.1	0.4	1.2	3.1	0.5	10.38	11.08	3.3				1.2	9.9	7.5
	MAX.	2.4	0.9	9.9	0.55	/	0.5	1.3	3.2	0.6	10.55	11.18	3.4				1.3	10	7.6
SYMBOL		E2	E3	E4	H	H1	K	L	L1	L2	L3	L4	P	θ	aaa	ccc	ddd	eee	
MILLIMETER	MIN.	0.3	8.5	9.46	11.5	6.55	4.08	1.6	0.5	0.5	1	0.13	2.85	10° REF	0.2	0.2	0.25	0.2	
	TYP.	0.4			11.68	6.65	4.18	1.9	0.7	0.6	1.2	0.23	3						
	MAX.	0.5			11.85	6.75	4.28	2.1	0.9	0.7	1.3	0.33	3.15						