Module connector
MS4-6-AMV

Part number: 543489



General operating condition

Data sheet

Feature	Value
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Temperature of medium	-10 °C ... 60 °C
Product weight	77 g
Note on materials	RoHS-compliant
Material of sub-base	Die-cast aluminum
Sealing ring material	NBR
Module connector material	Die-cast aluminum

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

DSBC-80-20-D3-PPSA-N3 QSS-8-F HGL-1/8-QS-6 NPQP-T-Q8-E-FD-P10 QS-1/8-8-I QSF-1/4-8-B VBQF-U-G14-E 153151 NPQH-T-Q14-E-P10 153367 NPQP-Y-R12-Q12-FD QSLL-G1/2-12 SGS-M10X1,25 NPQP-D-Q4-S8-FD-P10 NPQP-LQ-R18-Q4-FD-P10 SASC-P4-A-M8-A VABM-B10-25S-G38-6-P3 NPQP-L-Q10-E-FD-P10 QSY-6H-4 153307 NPQP-Y-Q6-E-FD-P10 QS-1/2-16 QSF-3/8-8-B VABM-B10-25S-G38-10 153031 QS-10H-6 QSML-6 NPQP-LQ-R18-Q8-FD-P10 153269 CRVZS-0.4