N-channel Enhancement Mode Power MOSFET

Features

- VDS= 60V, ID= 50A
  RDS(ON) < 12 mΩ @ VGS = 10V
  RDS(ON) < 16 mΩ @ VGS =4.5V

General Features

- Advanced Trench Technology
- Provide Excellent RDS(ON) and Low Gate Charge
- Lead Free and Green Available

100% UIS TESTED!
100% ΔVds TESTED!

RoHS



TO-252-2L Top View



Pin Assignment



Schematic Diagram

Absolute Maximum Ratings (T_C=25℃unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current-Continuous	I_D	50	A
Drain Current-Continuous(T_C=100℃)	I_D (100℃)	35.4	A
Pulsed Drain Current	I_{DM}	200	A
Maximum Power Dissipation	P_D	85	W
Derating factor		0.57	W/℃
Single pulse avalanche energy (Note 5)	E_{AS}	200	mJ
Operating Junction and Storage Temperature Range	T_J,T_{STG}	-55 To 175	℃

Thermal Characteristic

Thermal Resistance,Junction-to-Case(Note 2)	$R_{\theta JC}$	1.8	℃/W

Electrical Characteristics (T_C=25℃unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V I_D=250μA	60	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=60V,V_{GS}=0V	-	-	1	μA
Gate-Body Leakage Current	I_{GSS}	V_{GS}=±20V,V_{DS}=0V	-	-	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=250μA	1.0		3.0	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=10V, I_D=20A	-	12		mΩ
		V_{GS}=4.5V, I_D=20A	-	16		mΩ
Forward Transconductance	g_{FS}	V_{DS}=5V,I_D=20A	18	-	-	S
Dynamic Characteristics (Note4)						
Input Capacitance	C_{lss}	V_{DS}=30V,V_{GS}=0V, F=1.0MHz	-	1630	-	PF
Output Capacitance	C_{oss}		-	113	-	PF
Reverse Transfer Capacitance	C_{rss}		-	97	-	PF
Switching Characteristics (Note 4)						
Turn-on Delay Time	$t_{d(on)}$	V_{DD}=30V, R_L=6.7Ω V_{GS}=5V,R_G=3Ω	-	15	-	nS
Turn-on Rise Time	t_r		-	20	-	nS
Turn-Off Delay Time	$t_{d(off)}$		-	120	-	nS
Turn-Off Fall Time	t_f		-	15.6	-	nS
Turn-on Delay Time	$t_{d(on)}$	V_{DD}=30V, R_L=6.7Ω V_{GS}=10V,R_G=3Ω	-	7.4	-	nS
Turn-on Rise Time	t_r		-	5.1	-	nS
Turn-Off Delay Time	$t_{d(off)}$		-	28.2	-	nS
Turn-Off Fall Time	t_f		-	5.5	-	nS
Total Gate Charge	Q_g	V_{DS}=30V,I_D=20A, V_{GS}=10V	-	39		nC
Gate-Source Charge	Q_{gs}		-	7		nC
Gate-Drain Charge	Q_{gd}		-	8.5		nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V_{SD}	V_{GS}=0V,I_S=20A	-		1.2	V
Diode Forward Current (Note 2)	I_S		-	-	50	A
Reverse Recovery Time	t_{rr}	TJ = 25°C, IF =20A di/dt = 100A/μs(Note3)	-	28	-	nS
Reverse Recovery Charge	Qrr		-	40	-	nC
Forward Turn-On Time	t_{on}	Intrinsic turn-on time is negligible (turn-on is dominated by LS+LD)				

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t ≤ 10 sec.
3. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production
5. EAS condition : Tj=25℃,V_{DD}=30V,V_G=10V,L=0.5mH,Rg=25Ω

Typical Electrical and Thermal Characteristics (Curves)



Figure 1 Output Characteristics



Figure 4 Rdson-Junction Temperature



Figure 2 Transfer Characteristics



Figure 5 Gate Charge



Figure 3 Rdson- Drain Current



Figure 6 Source- Drain Diode Forward



Figure 7 Capacitance vs Vds



Figure 9 BV_{DSS} vs Junction Temperature



Figure 8 Safe Operation Area



Figure 10 $V_{GS(th)}$ vs Junction Temperature



Figure 11 Normalized Maximum Transient Thermal Impedance