
Air solenoid valve
VUVS-L30-M52-MD-N38-F8

Part number: 575647





General operating condition

Data sheet

Feature	Value
Valve function	5/2, monostable
Actuation type	Electrical
Valve size	31 mm
Standard nominal flow rate	2300 l/min
Pneumatic working port	3/8 NPT
Operating pressure	0.25 MPa ... 1 MPa
Operating pressure	2.5 bar ... 10 bar
Structural design	Piston gate valve
Reset method	Mechanical spring
Certification	c UL us - Recognized (OL)
Maritime classification	See certificate
Certificate issuing authority	DNVGL-TAA000011J
Nominal width	9.4 mm
Exhaust air function	With flow control option
Sealing principle	Soft
Mounting position	Any
Manual override	Detenting Non-detenting
Type of control	Pilot-controlled
Pilot air supply port	Internal
Flow direction	Non-reversible
Symbol	00991035
Lap	Overlap
b-value	0.4
C value	9.9 l/sbar
Switching time off	62 ms
On switching time	17 ms
Max. positive test pulse with 0 signal	2000 µs
Max. negative test pulse on 1 signal	3600 µs
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Vibration resistance	Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6
Shock resistance	Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
Temperature of medium	-10 °C ... 60 °C

Feature	Value
Pilot medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Ambient temperature	-10 °C ... 60 °C
Product weight	450 g
Type of mounting	Optionally: On terminal strip With through-hole
Venting hole connection	Not ducted
Pilot exhaust air port 82	10-32 UNF-2B
Pilot exhaust air port 84	10-32 UNF-2B
Pneumatic connection 1	3/8 NPT
Pneumatic connection 2	3/8 NPT
Pneumatic connection 3	3/8 NPT
Pneumatic connection 4	3/8 NPT
Pneumatic connection 5	3/8 NPT
Note on materials	RoHS-compliant
Seals material	HNBR NBR
Housing material	Die-cast aluminum Painted
Piston slide material	Wrought aluminum alloy
Material of screws	Steel, nickel-plated

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

DSBC-50-20-D3-PPSA-N3 QSL-12 VABM-L1-10HW-G18-4-GR 153034 QSLV-G1/8-8
DSBC-32-40-D3-PPVA-N3 NPQH-D-Q12-Q8-P10 NPQH-D-Q14-E-P10 NPQH-T-G38-Q8-P10
NPQP-D-R38-Q10-FD-P10 QS-G1/8-6-I QSLV-G1/2-12-I QSLV-G1/4-6 VABM-B10-25S-G38-4-P3
DFM-63-100-P-A-KF DSBC-40-160-D3-PPSA-N3 NPQP-D-R14-Q10-FD-P10 VABM-B10-20S-G14-6
VABM-L1-14W-G14-4-GR DSBC-32-50-D3-PPVA-N3 DSBC-40-50-D3-PPSA-N3 NPQH-D-S14-Q8-P10
VABM-B10-25S-G38-6 QS-G3/8-12 QSL-1/4-4 DSBC-63-320-D3-PPVA-N3 HGL-1/8-B SEA-3GS-M8-S
SPTW-P16R-G14-A-M12 VABM-L1-18S-G38-10