# 1-825437-0 ✔ ACTIVE

AMPMODU | AMPMODU Headers

TE Internal #: 1-825437-0

PCB Mount Header, Right Angle, Board-to-Board, 10 Position, 2.54 mm [.1 in] Centerline, Breakaway, AMPMODU Headers

View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Header**

PCB Mount Orientation: **Right Angle**

Connector System: **Board-to-Board**

Number of Positions: **10**

Number of Rows: **1**

## Features

### Product Type Features

| | |
|---|---|
| PCB Connector Assembly Type | PCB Mount Header |
| Connector System | Board-to-Board |
| Header Type | Breakaway |
| Sealable | No |
| Connector & Contact Terminates To | Printed Circuit Board |

### Configuration Features

| | |
|---|---|
| Connector Contact Load Condition | Fully Loaded |
| PCB Mount Orientation | Right Angle |
| Number of Positions | 10 |
| Number of Rows | 1 |
| Board-to-Board Configuration | Perpendicular |

### Electrical Characteristics

| | |
|---|---|
| Insulation Resistance | 5000 MΩ |
| Dielectric Withstanding Voltage (Max) | 750 Vrms |

### Body Features

| | |
|---|---|
| Primary Product Color | Green |

### Contact Features

| | |
|---|---|
| Mating Square Post Dimension | .64 mm[.025 in] |

| | |
|---|---|
| PCB Contact Termination Area Plating Material Thickness | 2.5 µm |
| Contact Shape & Form | Square |
| Contact Underplating Material | Nickel |
| PCB Contact Termination Area Plating Material | Tin |
| Contact Base Material | Brass |
| Contact Mating Area Plating Material | Gold or Gold Flash over Palladium Nickel |
| Contact Mating Area Plating Material Thickness | .8 µm[31.5 µin] |
| Contact Type | Pin |
| Contact Current Rating (Max) | 5 A |

## Termination Features

| | |
|---|---|
| Square Termination Post & Tail Dimension | .64 mm[.025 in] |
| Termination Post & Tail Length | 3.2 mm[.126 in] |
| Termination Method to PCB | Through Hole - Solder |

## Mechanical Attachment

| | |
|---|---|
| Mating Alignment | Without |
| PCB Mount Retention | Without |
| PCB Mount Alignment | Without |
| Connector Mounting Type | Board Mount |

## Housing Features

| | |
|---|---|
| Centerline (Pitch) | 2.54 mm[.1 in] |
| Housing Material | PBT |

## Dimensions

| | |
|---|---|
| PCB Thickness (Recommended) | 1.57 mm[.062 in] |

## Usage Conditions

| | |
|---|---|
| Housing Temperature Rating | Standard |
| Operating Temperature Range | -65 – 105 °C[-85 – 221 °F] |

## Operation/Application

| | |
|---|---|
| Circuit Application | Signal |

## Industry Standards

| | |
|---|---|
| Compatible With Agency/Standards Products | CSA, UL |
| Compatible With Approved Standards Products | CSA LR7189, UL E28476 |
| UL Flammability Rating | UL 94V-0 |

## Packaging Features

| | |
|---|---|
| Packaging Quantity | 300 |
| Packaging Method | Carton |

## Product Compliance

For compliance documentation, visit the product page on TE.com>

| | |
|---|---|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Wave solder capable to 265°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



TE Part # 1-925369-0
MOD 4 REC.HSG 1X10P


## Also in the Series | AMPMODU Headers



Connector Contacts(60)



Connector Hardware(1)



PCB Headers & Receptacles(1624)




Wire-to-Board Connector Assemblies & Housings(5)

## Customers Also Bought




TE Part #3-2158000-5
RZ01-1A4-D005-R



TE Part #103653-9
10 MTE SHRD PIN HSG SR LATCH



TE Part #6-104910-4
15 MTE HDR SRST LATCH .100CL



TE Part #1-2176315-5
MELF SMA_A 1K5 0.1% 15PPM 0204 0.4W



TE Part #133039-E
MJ DS-LG5 * * 8 8 2 * GF9 * * 30 5 J 3 1




TE Part #5-1478763-1
Metal backshell 9 way 45 Deg E

TE Part #9-1415899-3
RZ01-1A4-D012-R

## Documents

### CAD Files

3D PDF

3D

Customer View Model
ENG_CVM_CVM_1-825437-0_V.2d_dxf.zip

English

Customer View Model
ENG_CVM_CVM_1-825437-0_V.3d_igs.zip

English

Customer View Model
ENG_CVM_CVM_1-825437-0_V.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

### Agency Approvals

UL Report

English

# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## TE Connectivity:

2310537-1 2834055-1 ROX05SJ18R SBCHE154R7K SMW73R0JT TE50BR39J 936348-1 2380312-2
3430B2F51RTDF U5254-000005-030PA 141991-2 3631B101LL 650075-000 917696-1 CPF0402B37K4E1
1-794222-0 1743455-2 1903112-2 MPT100C18RF RH73H2A40MKTN 1393431-1 175977-2 1969656-1
2-292161-3 2377783-2 1-962915-1 2005330-1 3-1393225-0 CRGCQ2010J3K3 SBCHE64R7K