Pulse a YAGEO company

CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series

Automotive AEC-Q200

RoHS Compliant
Halogen Free
REACH Compliant





Noise Suppression | Unshield | Wire Wound | Ferrite | General Signal line

■ Part Numbering

A	WCU	00	201212	300	M	02
Grade	Series Name	Control Code	Dimensions Code (mm)	Impedance (Ω)	Tolerance	Internal Code
			2.05x1.25x1.2	300 30	M ±20%	02 USB2.0
			3.2x1.6x1.9	121 120	Y ±25%	03 USB3.0

A	WCU	00	453226	510	X	G0
Grade	Series Name	Control Code	Dimensions Code (mm)	Inductance (uH)	Tolerance	Internal Code
			3.3x2.5x2.3	110 11	T ±30%	G0
			3.3x2.5x2.5	510 51	X -	TE
			4.5x3.2x2.6	101 100		T2
			4.5x3.2x2.8			MF

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive
AEC-Q200

AWCU00201212-02 Type

■ Dimensions / Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics

Part No.	Impedance (Ω)	Test Freq. (MHz)	RDC (Ω)Max.	IDC (mA)	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.	Tolerance (±%)
AWCU00201212300□02	30	100	0.2	450	50	125	10	20,25
AWCU00201212670□02	67	100	0.25	400	50	125	10	20,25
AWCU00201212750□02	75	100	0.3	360	50	125	10	20,25
AWCU00201212900□02	90	100	0.35	330	50	125	10	20,25
AWCU00201212121□02	120	100	0.3	400	50	125	10	20,25
AWCU00201212161□02	160	100	0.35	350	50	125	10	20,25
AWCU00201212181□02	180	100	0.35	330	50	125	10	20,25
AWCU00201212201□02	200	100	0.35	330	50	125	10	20,25
AWCU00201212221□02	220	100	0.35	310	50	125	10	20,25
AWCU00201212261□02	260	100	0.4	300	50	125	10	20,25
AWCU00201212301□02	300	100	0.4	290	50	125	10	20,25
AWCU00201212361□02	360	100	0.45	280	50	125	10	20,25
AWCU00201212371□02	370	100	0.45	280	50	125	10	20,25
AWCU00201212501□02	500	100	0.55	170	50	125	10	20,25
AWCU00201212671□02	670	100	0.6	140	50	125	10	20,25
AWCU00201212901□02	900	100	0.6	80	50	125	10	20,25

Note: When ordering, please specify tolerance code. Tolerance: M=±20% Y=±25%

1. Operating temperature range －50℃～150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. IDC for Inductance drop 10% from its value without current.
4. Measure Equipment:
   Z: Agilent HP4287A+Agilent 16197A
   RDC: Chroma 16502 (Single Wire Test Value)
   IDC: HP4284A+HP42841A/HP4285A+HP42841A


Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Commom Mode Choke AWCU Series

Automotive
AEC-Q200

AWCU00201212-02 Type

■ Characteristics Graph



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive
AEC-Q200

AWCU00321619-02 Type

■ Dimensions / Recommended Land Pattern



■ NO Polarity Equivalent circuit



■ Electrical Characteristics

Part No.	Impedance (Ω)	Test Freq. (MHz)	RDC (Ω)Max.	IDC (mA)	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.	Tolerance (±%)
AWCU00321619900□02	90	100	0.3	370	50	125	10	20
AWCU00321619121□02	120	100	0.3	370	50	125	10	20
AWCU00321619161□02	160	100	0.4	340	50	125	10	20
AWCU00321619221□02	220	100	0.4	320	50	125	10	20
AWCU00321619261□02	260	100	0.5	310	50	125	10	20
AWCU00321619601□02	600	100	0.8	260	50	125	10	20
AWCU00321619102□02	1000	100	1	230	50	125	10	20
AWCU00321619222□02	2200	100	1.2	200	50	125	10	20

Note: When ordering, please specify tolerance code. Tolerance: M=±20%

1. Operating temperature range －50℃～150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. IDC for Inductance drop 10% from its value without current.
4. Measure Equipment:
   Z: Agilent HP4287A+Agilent 16197A
   RDC: Chroma 16502 (Single Wire Test Value)
   IDC: HP4284A+HP42841A/HP4285A+HP42841A

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series

Automotive
AEC-Q200

AWCU00321619-02 Type

■ Characteristics Graph



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive
AEC-Q200

AWCU00332523 Type

■ Dimensions / Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics

Part No.	Impedance (Ω)10MHz Min.(Typ.)	Inductance (uH)+50/-30%	Stary Inductance (uH)Typ.	Test Freq.	RDC (Ω)Max.	Irms (mA)Max.	Rated Voltage (Vdc)Max.	Insulation Resistance (MΩ)Min.
AWCU00332523110XT2	300(550)	11	0.05	100kHz	0.4	300	80	10
AWCU00332523220XT2	500(1100)	22	0.06	100kHz	0.5	250	80	10
AWCU00332523510XT2	1000(2600)	51	0.09	100kHz	0.7	200	80	10
AWCU00332523101XT2	2200(5100)	100	0.13	100kHz	1.5	150	80	10

Note:

1. Operating temperature range －50℃～150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 15℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B

■ Electrical Characteristics

Part No.	Inductance (uH)+50/-30%	Test Freq.	RDC (Ω)Max.	Irms (mA)Max.	Rated Voltage (Vdc)	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.
AWCU00332523101XMF	100	100kHz	2.2	115	50	125	10

Note:

1. Operating temperature range －40℃～125℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 15℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.


Commom Mode Choke AWCU Series

Automotive
AEC-Q200

AWCU00332523 Type

■ Characteristics Graph





Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive
AEC-Q200

AWCU00332525 Type

■ Dimensions / Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics

Part No.	Impedance (Ω)10MHz Min.(Typ.)	Inductance (uH)+50/-30%	Stary Inductance (uH)Typ.	Test Freq.	RDC (Ω)Max.	Irms (mA)Max.	Rated Voltage (Vdc)Max.	Insulation Resistance (MΩ)Min.
AWCU00332525110XG0	300(550)	11	0.05	100kHz	0.4	300	80	10
AWCU00332525220XG0	500(1100)	22	0.06	100kHz	0.5	250	80	10
AWCU00332525510XG0	1000(2600)	51	0.09	100kHz	0.7	200	80	10
AWCU00332525101XG0	2200(5100)	100	0.13	100kHz	1.5	150	80	10

Note:

1. Operating temperature range －50℃～150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 15℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series

Automotive
AEC-Q200

AWCU00332525 Type

■ Characteristics Graph



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.


Pulse a YAGEO company

CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series

AWCU00332525-TE Type

■ Dimensions / Recommended Land Pattern ■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics

Part No.	L 100KHz,0.1V (uH)	RDC (Ω) Max(typ)	Irms (mA) Max.	Insulation Resistance (MΩ)Min.	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)Max.	Tolerance (±%)
AWCU00332525800□TE	80	2.6(2.1)	100	10	80	125	X,T
AWCU00332525101□TE	100	3.0(2.4)	120	10	80	125	X,T
AWCU00332525201□TE	200	5.5(4.6)	70	10	80	150	X,T

Note: When ordering, please specify tolerance code. Tolerance: X=+50% to -20%, T=+30% to -10%

1. Operating temperature range －55℃～125℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 15℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series

Automotive
AEC-Q200

AWCU00332525-TE Type

■ Characteristics Graph



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive
AEC-Q200

AWCU00453226-T2 Type

■ Dimensions/Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics

Part No.	Inductance (uH)	Test Freq.	Impedance (Ω) Min.	Impedance (Ω) Typ.	Test Freq. (MHz)	RDC (Ω) Max.	Irms (mA) Max.	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.	Tol. (±%)
AWCU00453226113□T2	11	100kHz	300	600	10	0.6	250	50	125	10	30
AWCU00453226223□T2	22	100kHz	500	1200	10	1	200	50	125	10	30
AWCU00453226513□T2	51	100kHz	1000	2800	10	1	200	50	125	10	30
AWCU00453226104□T2	100	100kHz	2000	5800	10	2	150	50	125	10	30

Note: When ordering, please specify tolerance code. Tolerance: T=±30%

1. Operating temperature range －50℃～150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 40℃ rise above 25℃ ambient.
4. Measure Equipment:
   Z: HP4286A / HP4287A / AgilentE4991A
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series

Automotive
AEC-Q200

AWCU00453226-T2 Type

■ Characteristics Graph



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive
AEC-Q200

AWCU00453226-G0 Type

■ Dimensions / Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics

Part No.	Inductance1 (uH) 100kHz(50/-30%)	Inductance2 (uH) 1MHz(Typ.)	Impedance (Ω) 10MHz(Typ.)	RDC (Ω)Max.	Irms (mA)Max.	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.
AWCU00453226110XG0	11	-	670	0.5	360	50	125	10
AWCU00453226220XG0	22	-	1450	0.6	310	50	125	10
AWCU00453226510XG0	51	51	3500	1	230	50	125	10
AWCU00453226101XG0	100	100	6500	2	200	50	125	10

1. Operating temperature range －50℃～150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 40℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series

Automotive
AEC-Q200

AWCU00453226-G0 Type

■ Characteristics Graph



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive
AEC-Q200

AWCU00453228 Type

■ Dimensions / Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics

Part No.	Inductance (uH)+50/-25%	Test Freq.	RDC (Ω)Max.	Irms (mA)Max.	Rated Voltage (Vdc)Max.	Insulation Resistance (MΩ)Min.
AWCU00453228201XTE	200	100kHz	4.5	100	50	10

Note:

1. Operating temperature range －40℃～125℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. Irms for 15℃ rise above 25℃ ambient.
4. Measure Equipment:
   L: HP4284A+HP42841A/HP4285A+HP42841A
   RDC: CHROMA MILLIOM METER MODE 16502
   Irms: HP4284A+HP42841A/HP4285A+HP42841A
   Insulation Resistance: HP4339B

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series

Automotive
AEC-Q200

AWCU00453228 Type

■ Characteristics Graph



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive
AEC-Q200

AWCU00201212-03 Type

■ Dimensions / Recommended Land Pattern



■ NO Polarity Equivalent circuit



unit:mm

■ Electrical Characteristics

Part No.	Impedance (Ω)	Test Freq. (MHz)	RDC (Ω)Max.	IDC (mA)	Rated Voltage (Vdc)Max.	Withstanding Voltage (Vdc)	Insulation Resistance (MΩ)Min.	Tolerance (±%)
AWCU00201212500□03	50	100	0.2	500	50	125	10	20,25
AWCU00201212670□03	67	100	0.3	500	50	125	10	20,25
AWCU00201212900□03	90	100	0.3	500	50	125	10	20,25
AWCU00201212121□03	120	100	0.35	330	50	125	10	20,25

Note: When ordering, please specify tolerance code. Tolerance: M=±20% Y=±25%

1. Operating temperature range －50℃～150℃(Including self - temperature rise)
2. RDC: SINGLE WIRE TEST VALUE
3. IDC for Inductance drop 10% from its value without current.
4. Measure Equipment:
   Z: Agilent HP4287A+Agilent 16197A
   RDC: Chroma 16502 (Single Wire Test Value)
   IDC: HP4284A+HP42841A/HP4285A+HP42841A

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series

Automotive
AEC-Q200

AWCU00201212-03 Type

■ Characteristics Graph



Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive AEC-Q200

AWCU00201212500Y03


■ Insertion Loss For HDMI2.0 Testing:



■ Insertion Loss For USB3.0 Testing:




■ TDR For HDMI2.0 Testing:




Parameter Name: HDMI2.0 Choke Impedance c1	
Spc Max: 115 Ω	Spc Min: 85 Ω
Max:100.73 Ohms at 0.7552 ns	Min:91.30 Ohms at 0.4827 ns
ΔΩ: 9.43	Avg: 96.02 Ohms
	Result: Pass

■ TDR For USB3.0 Testing:




Parameter Name: Choke Impedance C1	
Spc Max: 105 Ω	Spc Min: 75 Ω
Max:100.25 Ohms at 0.6200 ns	Min:86.88 Ohms at 0.4825 ns
ΔΩ: 13.36	Avg: 93.57 Ohms
	Result: Pass

■ Eye DiagramFor HDMI2.0 Testing:



Parameter Name: HDMI2.0 Choke Eye Diagram with 25ps c1	
Display Mode: Not a standard mode	
dRate: 6 Gbits/s; 166.7 ps	Vi: 500 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass

■ Eye DiagramFor USB3.0 Testing:



Parameter Name: USB3.0 Choke Eye Diagram C1	
Display Mode: Not a standard mode	
dRate: 5 Gbits/s; 200.0 ps	Vi: 250 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive
AEC-Q200

AWCU00201212670Y03


■ Insertion Loss For HDMI2.0 Testing:



■ Insertion Loss For USB3.0 Testing:




■ TDR For HDMI2.0 Testing:




Parameter Name: HDMI2.0 Choke Impedance c1	
Spc Max: 115 Ω	Spc Min: 85 Ω
Max:100.99 Ohms at 0.6645 ns	Min:90.10 Ohms at 0.4614 ns
ΔΩ: 10.89	Avg: 95.54 Ohms
	Result: Pass

■ TDR For USB3.0 Testing:




Parameter Name: Choke Impedance C1	
Spc Max: 105 Ω	Spc Min: 75 Ω
Max:101.51 Ohms at 0.6150 ns	Min:82.65 Ohms at 0.4775 ns
ΔΩ: 18.86	Avg: 92.08 Ohms
	Result: Pass

■ Eye DiagramFor HDMI2.0 Testing:



Parameter Name: HDMI2.0 Choke Eye Diagram with 25ps c1	
Display Mode: Not a standard mode	
dRate: 6 Gbits/s; 166.7 ps	V: 500 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass

■ Eye DiagramFor USB3.0 Testing:



Parameter Name: USB3.0 Choke Eye Diagram C1	
Display Mode: Not a standard mode	
dRate: 5 Gbits/s; 200.0 ps	V: 250 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive AEC-Q200

AWCU00201212900Y03


■ Insertion Loss For HDMI2.0 Testing:



■ Insertion Loss For USB3.0 Testing:




■ TDR For HDMI2.0 Testing:




Parameter Name: HDMI2.0 Choke Impedance c1	
Spc Max: 115 Ω	Spc Min: 85 Ω
Max:100.15 Ohms at 0.7552 ns	Min:85.35 Ohms at 0.5202 ns
ΔΩ: 14.80	Avg: 92.75 Ohms
	Result: Pass

■ TDR For USB3.0 Testing:




Parameter Name: Choke Impedance C1	
Spc Max: 105 Ω	Spc Min: 75 Ω
Max:98.68 Ohms at 0.3738 ns	Min:79.36 Ohms at 0.5238 ns
ΔΩ: 19.33	Avg: 89.02 Ohms
	Result: Pass

■ Eye DiagramFor HDMI2.0 Testing:



Parameter Name: HDMI2.0 Choke Eye Diagram with 25ps c1	
Display Mode: Not a standard mode	
dRate: 6 Gbits/s; 166.7 ps	V: 500 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass

■ Eye DiagramFor USB3.0 Testing:



Parameter Name: USB3.0 Choke Eye Diagram C1	
Display Mode: Not a standard mode	
dRate: 5 Gbits/s; 200.0 ps	V: 250 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Pulse a YAGEO company


CHILISIN ELECTRONICS CORP.

Commom Mode Choke AWCU Series


Automotive
AEC-Q200

AWCU00201212121Y03


■ Insertion Loss For HDMI2.0 Testing:



■ Insertion Loss For USB3.0 Testing:




■ TDR For HDMI2.0 Testing:




Parameter Name: HDMI2.0 Choke Impedance c1	
Spc Max: 115 Ω	Spc Min: 85 Ω
Max:101.21 Ohms at 0.7077 ns	Min:91.02 Ohms at 0.4927 ns
ΔΩ: 10.19	Avg: 96.12 Ohms
	Result: Pass

■ TDR For USB3.0 Testing:




Parameter Name: Choke Impedance C1	
Spc Max: 105 Ω	Spc Min: 75 Ω
Max:100.24 Ohms at 0.6263 ns	Min:85.90 Ohms at 0.5275 ns
ΔΩ: 14.35	Avg: 93.07 Ohms
	Result: Pass

■ Eye DiagramFor HDMI2.0 Testing:



Parameter Name: HDMI2.0 Choke Eye Diagram with 25ps c1	
Display Mode: Not a standard mode	
dRate: 6 Gbits/s; 166.7 ps	V: 500 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass

■ Eye DiagramFor USB3.0 Testing:



Parameter Name: USB3.0 Choke Eye Diagram C1	
Display Mode: Not a standard mode	
dRate: 5 Gbits/s; 200.0 ps	V: 250 mV;Gain: 0 dB;Off: 0 mV
CAL: DONE,JGen: OFF	Result: Pass


Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Commom Mode Choke AWCU Series

Automotive
AEC-Q200

Packaging

Tape Dimensions



Reel Dimensions

Figure1





Figure 2



Dimensions in mm

TYPE	Tape Dimensions										Reel Dimensions					Quantity
	A0	B0	K0	D	E	F	W	P	P0	P2	Fig.	A	B	C	D	PCS/REEL
AWCU00201212	1.5	2.25	1.45	1.5	1.75	3.5	8	4	2	2	1	178	60	12	1.5	2000
AWCU00321619	1.76	3.47	2.05	1.5	1.75	3.5	8	4	2	2	1	178	60	12	1.5	2000
AWCU00332523	2.72	3.52	2.45	1.5	1.75	5.5	12	4	4	2	1	178	60	16	1.5	1500
AWCU00332525	2.72	3.52	2.60	1.5	1.75	5.5	12	4	4	2	1	178	60	16	1.5	1500
AWCU00332525_TE	2.72	3.52	2.60	1.5	1.75	5.5	12	4	4	2	1	178	60	16	1.5	2000
AWCU00453226	3.6	4.9	3	1.5	1.75	5.5	12	8	4	2	2	330	100	13	13.4	2500
AWCU00453228	3.6	4.9	3	1.5	1.75	5.5	12	8	4	2	2	330	100	13	13.4	2500

Please be sure to request approval specifications that provide further details of the products. Kindly note that the content of these specifications are subject to change or may be discontinued without prior notice. This product may not be designed/used in medical or high risk applications without Chilisin approval. Please contact our sales department before ordering.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Pulse Electronics:

PD380-4000S1NF PD617-6000M243 ANT1204F007R0870A E5J88-032-02-L PA4320.334NLT BDHE002520122R2MQ1 PA4341.301NLT W3078 BSPQ000603043N0B00 PA2744NL PAT6261.003NLT PE-68386NLT PG2290.151HLT DPX1608LKF3R2460A PA0369NL PE-67100NL PGL6395.121HLT W3334B0150 W1093 W1902 AWCS0012070736NJ00 BBUP00201209121Y00 P0585NL PA4343.361NLT PA4343.451NLT BSPQ000603041N4B00 PA4341.221NLT JXD0-2015NL JXD2-0Z10NL PA4320.104NLT