
MRSS - MINIATURE ROTARY SWITCH SERIES

PRODUCT DESCRIPTION

The MRSS addresses manual programming applications. These high-quality rotary DIP switches are available in size 7.7mm square (horizontal) and 7.2mm square (vertical) for a wide range of possible applications like elevator and security system. Meanwhile the compact design offers 50% lower profile than standard DIP switches and save space around 40% PCB area. In addition, MRD Series provide more options for terminal, hexadecimal or binary code, with or without complement types to fulfill the variety requirements.

The MRSS Switches are characterised by contact rating of 0.4VA @ 20V DC or AC.

Reference TE customer drawing for application instructions.



FEATURES

- Offer both SMD and THT
- Space saving with a low profile
- High reliability with 2 points contacts
- Hexadecimal or binary code, with complement
- Vertical and horizonal versions
- MSL 1 conformance
- Packaged in Tube and Tape/Reel

APPLICATION

- Elevator
- Single chip
- Security system
- Lighting system
- Machinery
- Telecommunication

MRSS - Miniature rotary switch series


MRSS Series – Type Classification

Rating		0.4VA @ 20V DC or AC MAX.
Contact Resistance		100mΩ MAX @2VDC 10mA initial
Operation Temperature		-40°C to 85°C
Mechanical Life		10,000 steps
Electrical Life		10,000 steps @ 5VDC, 10mA
Withstanding Voltage		250VAC for 1 min
Operation Force		2.0mN-m MIN, 19.6mN·m MAX.
Soldering Conditions	**Manual**	Temp of iron tip: 320°C MAX. for 4±1 sec
	Flow	Preheat 100 to 105°C for 30±5 sec Solder temp 265°C ±3°C for 8±2 sec
	Reflow	Preheat 160 to 190°C for 90 to 120 sec Reflow temp 225°C (switch surface) for 20 to 60 sec Peak temp 255°C (switch surface) MAX.

Material Specifications

Components	Material	Finish	Components	Material	Finish
Case	PSS	Color: Black	Fixed contact	Cu alloy	Au flash
Frame	PSS	Color: Light Brown, Black	Movable contact	Cu alloy	Au plated
Rotar	LCP	Color: White	Holder	SUS	Silver
Plate	SUS	-	-	-	-

Circuit type



Terminal Identification viewed from bottom switch

MRSS - Miniature rotary switch series

R - Real code. 10 and 16 positions.

BDC

CODE	Position									
	0	1	2	3	4	5	6	7	8	9
1		●		●		●		●		●
2			●	●			●	●		
4					●	●	●	●		
8									●	●

Hexadecimal

CODE	Position															
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
1		●		●		●		●		●		●		●		●
2			●	●			●	●			●	●			●	●
4					●	●	●	●					●	●	●	●
8									●	●	●	●	●	●	●	●

C - Complement code. 10 and 16 positions.

BDC Complement

CODE	Position									
	0	1	2	3	4	5	6	7	8	9
1	●		●		●		●		●	
2	●	●			●	●			●	●
4	●	●	●	●					●	●
8	●	●	●	●	●	●	●	●		

Hexadecimal Complement

CODE	Position															
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
1	●		●		●		●		●		●		●		●	
2	●	●			●	●			●	●			●	●		
4	●	●	●	●					●	●	●	●				
8	●	●	●	●	●	●	●	●								

G - Gray code. 10 and 16 positions.

BDC Gray

CODE	Position									
	0	1	2	3	4	5	6	7	8	9
1		●	●			●	●			●
2			●	●	●	●				
4					●	●	●	●	●	●
8									●	●


Hexadecimal Gray


CODE	Position															
	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
1		●	●			●	●			●	●			●	●	
2			●	●	●	●					●	●	●	●		
4					●	●	●	●	●	●	●	●				
8									●	●	●	●	●	●	●	●

MRSS - Miniature rotary switch series

Terminal


TH - Vertical, through hole TH (Hexadecimal)







SMGW - Vertical, gullwing SM (Hexadecimal)







SMJ - Vertical, J-Lead SM (Binary)





SMGW - Horizonal, gullwing SM (Binary)





ORDERING INFORMATION

Part Number

MRSS - __ __ __ __ __ __ __ __

Actuator Orientation

V	Vertical
H	Horizontal

Configuration/Pitch/Colour Cover or Bracket/Marking

0	DIP/2.54/Gray/LASER
1	DIP/2.54/Black/Printed
4	SIP/1.27/Stainless Steel/LASER

Actuator Type

D	Screw driver slot, Flush

Code

C	Complement
G	Gray
R	Real

Packaging

T	Tube
TR	Tape and reel

Solder Terminal Configuration

J	J-Lead
GW	Gullwing
Blank	Through Hole

Termination Type

SM	Surface Mount
TH	Through Hole

Position

10
16

te.com

©2022 TE Connectivity. All Rights Reserved.

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

06/23 ED

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

3430B2F51RTDF SBCHE154R7K 1743455-2 3-1393225-0 MPT100C18RF 1969656-1 RH73H2A40MKTN SBCHE64R7K TE50BR39J U5254-000005-030PA 1393431-1 141991-2 2-292161-3 2834055-1 936348-1 CPF0402B37K4E1 1-962915-1 1903112-2 2310537-1 2380312-2 650075-000 CRGCQ2010J3K3 3631B101LL 917696-1 ROX05SJ18R 1-794222-0 175977-2 2005330-1 SMW73R0JT 2377783-2