DESCRIPTION

The KPESDxxS1BA is designed for applications requiring transient overvoltage protection capability. They are intended for use in voltage and ESD sensitive equipment such as computers, printers, business machines, communication systems, medical equipment and other applications. These devices are ideal for situations where board space is at a premium.

This series has been specifically designed to protect sensitive components which are connected to power、data and transmission lines from overvoltage caused by ESD(electrostatic discharge), CDE (Cable Discharge Events),and EFT (electrical fast transients).

FEATURES

✧IEC61000-4-2 (ESD) ±15kV (air), ±8kV (contact)
✧IEC61000-4-4 (EFT) 40A (5/50ηs)
✧350 Watts Peak Pulse Power per (tp=8/20μs)
✧Protects one I/O line (bidirectional)
✧Low clamping voltage
✧Low leakage current

MACHANICAL DATA

✧SOD-323 package
✧Flammability Rating: UL 94V-0
✧Packaging: Tape and Reel
✧High temperature soldering guaranted:260℃/10s
✧Reel size: 7 inch


ORDERING INFORMATION

✧Device: KPESDxxS1BA
✧Package: SOD-323
✧Material: Halogen free
✧Packing: Tape & Reel
✧Quantity per reel: 3,000pcs

APPLICATIONS

✧Cell Phone Handsets and Accessories
✧Microprocessor based equipment
✧Personal Digital Assistants (PDA's)
✧Notebooks, Desktops, and Servers
✧Portable Instrumentation
✧Networking and Telecom
✧Serial and Parallel Ports.
✧Peripherals

PIN CONFIGURATION



PACKAGE OUTLINE




ABSOLUTE MAXIMUM RATING

Symbol	Parameter	Value	Units
V_{ESD}	ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	±15 ±8	kV
P_{PP}	Peak Pulse Power (8/20μs)	350	W
T_{OPT}	Operating Temperature	-55/+150	°C
T_{STG}	Storage Temperature	-55/+150	°C
T_L	Lead Soldering Temperature	260 (10 sec.)	°C


ELECTRICAL CHARACTERISTICS (Tamb=25°C)

PART NUMBER	DEVICE MARKING	V_{RWM} (V) (max.)	V_B (V) (min.)	I_T (mA)	V_C@1A (V) (max.)	V_C (V) (max.)	(@A)	I_R (μA) (max.)	C_T (pF) (max.)
KPESD3V3S1BA	2A	3.3	4.0	1	7.5	10.5	20	40	450
KPESD5V0S1BA	2B	5.0	6.0	1	9.8	18.0	17	10	200
KPESD12VS1BA	2D	12.0	13.3	1	19.0	32.0	11	1	75
KPESD15VS1BA	2J	15.0	16.7	1	24.0	38.0	10	1	68
KPESD18VS1BA	2K	18.0	20.0	1	29.0	45.0	9	1	57
KPESD24VS1BA	2H	24.0	26.7	1	43.0	52.0	7	1	50
KPESD36VS1BA	2N	36.0	40.0	1	60.0	75.0	5	1	35


ELECTRICAL CHARACTERISTICS CURVE




Pulse Waveform



Non-Repetitive Peak Pulse Power vs. Pulse Time





Power Derating Curve




Junction Capacitance vs. Reverse Voltage


SOD-323 PACKAGE OUTLINE DIMENSIONS







Symbol	Dimensions In Millimeters	
	Min	Max
A		1.00
A1	0.000	0.100
A2	0.800	0.900
b	0.250	0.350
c	0.080	0.150
D	1.200	1.400
E	1.600	1.800
E1	2.500	2.700
e	1.800	2.040
L	0.475 REF	
L1	0.250	0.400
θ	0°	8°



Recommended Pad outline

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

KUU:

KMOV0402E180C030T MSMD050/24 MSMD150 SMBJ17A SMF15A K1N5819HW-7-F SMDJ16A B340A ESD3V3D523-2U SJD12C15L01 SD103AWS S4 SMDJ7.0A SMDJ8.5A WNM4002-3/TR 1N5819W S4 1N60PW SMBJ6.0CA SMDJ7.5CA LSMD150 PESD12VS1UB SM712.TCT SMBJ160CA GBLC15CI KNTC0603/10KF3950 LSMD050 SMDJ9.0A BV03C ESD0301BU ESD05V32D-LC MBR0540-7-F