Quick connector
CK-1/2-PK-13

Part number: 4098



General operating condition

Data sheet

Feature	Value
Nominal width	11.7 mm
Type of seal on screwed plug	Sealing ring
Mounting position	Any
Design	Straight design
Operating pressure for entire temperature range	-0.095 MPa ... 1 MPa
Operating pressure for entire temperature range	-0.95 bar ... 10 bar
Operating pressure for entire temperature range	-13.775 psi ... 145 psi
Information on operating pressure	Water: max. 0.6 MPa at max. 50 °C
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-] Water (liquid, ice-free)
Information on operating and pilot media	Operation with oil lubrication possible Water: G-thread only possible with sealing ring type OL as additional accessory
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-10 °C ... 60 °C
Nominal tightening torque	14 Nm
Tolerance for nominal tightening torque	± 20%
Pneumatic connection 1	External thread G1/2
Pneumatic connection 2	for barbed fitting, inside diameter 13 mm, with nut
Material of union nut	Wrought aluminum alloy, anodized
Material of screwed plug	Anodized wrought aluminum alloy
Note on materials	RoHS-compliant
Sealing ring material	Reinforced PA TPE-U(PU)

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

NPQP-LQ-R18-Q4-FD-P10 QSLL-1/4-4 QSML-3 DSBC-32-50-D3-PPVA-N3 QH-1 1/2 DSBC-80-320-D3-PPVA-N3 N-1/8-P-6 NPQP-LQ-R18-Q8-FD-P10 QS-1/2-16 DSBC-80-250-D3-PPSA-N3 NPQP-D-Q4-S8-FD-P10 PUN-H-4X0,75-TBL SNC-63 DSBC-63-320-D3-PPVA-N3 MSFW-110-50/60-DS QSS-8-F SPTE-V1R-Q3-V-2.5K VABM-L1-18W-G38-8-G NPQP-L-Q10-E-FD-P10 CRVZS-0.4 DSBC-32-40-D3-PPVA-N3 DSNU-12-60-P-A NPQH-T-G38-Q8-P10 QSLV-G1/4-6 DSBC-50-20-D3-PPSA-N3 NPQP-Y-Q6-E-FD-P10 QSML-6 VBQF-U-G14-E DFM-63-100-P-A-KF NPQP-Y-R12-Q12-FD