
MOSFET – N-Channel, DUAL COOL® DFN8, POWERTRENCH®
40 V, 192 A, 1.1 mΩ

FDMS8320LDC



DFN8
DUAL COOL
CASE 506EG

Features
- Max $R_{DS(on)}$ = 1.1 mΩ at V_{GS} = 10 V, I_D = 44 A
- Max $R_{DS(on)}$ = 1.5 mΩ at V_{GS} = 4.5 V, I_D = 37 A
- Advanced Package and Silicon Combination for Low $R_{DS(on)}$ and High Efficiency
- Next Generation Enhanced Body Diode Technology, Engineered for Soft Recovery
- MSL1 Robust Package Design
- 100% UIL Tested
- This Device is Pb−Free, Halogen Free and RoHS Compliant


Applications
- OringFET/Load Switching
- Synchronous Rectification
- DC−DC Conversion

MOSFET MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)


Symbol	Parameter	Ratings	Unit
V_{DSS}	Drain−to−Source Voltage	40	V
V_{GS}	Gate−to−Source Voltage	±20	V
I_D	Drain Current – Continuous T_C = 25°C – Continuous T_A = 25°C (Note 1a) – Pulsed (Note 4)	 192 44 300	A
E_{AS}	Single Pulse Avalanche Energy (Note 3)	661	mJ
P_D	Power Dissipation, T_C = 25°C	125	W
	Power Dissipation, T_A = 25°C (Note 1a)	3.2	
T_J, T_{STG}	Operating and Storage Junction Temperature Range	−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

MARKING DIAGRAM



2G = Specific Device Code
A = Assembly Location
Y = Year
W = Work Week
Z = Assembly Lot Code



ORDERING INFORMATION
See detailed ordering and shipping information on page 6 of this data sheet.

© Semiconductor Components Industries, LLC, 2012

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
OFF CHARACTERISTICS						
BV_{DSS}	Drain−to−Source Breakdown Voltage	I_D = 250 μA, V_{GS} = 0 V	40	–	–	V
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temperature Coefficient	I_D = 250 μA, referenced to 25°C	–	22	–	mV/°C
I_{DSS}	Zero Gate Voltage Drain Corrent	V_{DS} = 32 V, V_{GS} = 0 V	–	–	1	μA
I_{GSS}	Gate−to−Source Leakage Current	V_{GS} = ±20 V, V_{DS} = 0 V	–	–	100	nA
ON CHARACTERISTICS						
$V_{GS(th)}$	Gate−to−Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 250 μA	1.0	1.6	3.0	V
$\Delta V_{GS(th)}/\Delta T_J$	Gate−to−Source Threshold Voltage Temperature Coefficient	I_D = 250 μA, referenced to 25°C	–	−6	–	mV/°C
$R_{DS(on)}$	Static Drain−to−Source On Resistance	V_{GS} = 10 V, I_D = 44 A	–	0.8	1.1	mΩ
		V_{GS} = 4.5 V, I_D = 37 A	–	1.1	1.5	
		V_{GS} = 10 V, I_D = 44 A, T_J = 125°C	–	1.2	1.7	
g_{FS}	Forward Transconductance	V_{DS} = 5 V, I_D = 44 A	–	244	–	S
DYNAMIC CHARACTERISTICS						
C_{iss}	Input Capacitance	V_{DS} = 20 V, V_{GS} = 0 V, f = 1 MHz	–	8310	11635	pF
C_{oss}	Output Capacitance		–	2255	3160	pF
C_{rss}	Reverse Transfer Capacitance		–	132	185	pF
R_g	Gate Resistance	f = 1 MHz	0.1	1.4	2.6	Ω
SWITCHING CHARACTERISTICS						
$t_{d(on)}$	Turn−On Delay Time	V_{DD} = 20 V, I_D = 44 A, V_{GS} = 10 V, R_{GEN} = 6 Ω	–	19	34	ns
t_r	Rise Time		–	15	27	ns
$t_{d(off)}$	Turn−Off Delay Time		–	69	110	ns
t_f	Fall Time		–	14	25	ns
$Q_{g(ToT)}$	Total Gate Charge	V_{GS} = 0 to 10 V, V_{DD} = 20 V, I_D = 44 A	–	121	170	nC
$Q_{g(ToT)}$	Total Gate Charge	V_{GS} = 0 to 4.5 V, V_{DD} = 20 V, I_D = 44 A	–	57	80	nC
Q_{gs}	Gate−to−Source Charge	V_{DD} = 20 V, I_D = 44 A	–	21	–	nC
Q_{gd}	Gate−to−Drain “Miller” Charge	V_{DD} = 20 V, I_D = 44 A	–	16	–	nC
DRAIN−SOURCE DIODE CHARACTERISTIC						
V_{SD}	Source−to−Drain Diode Forward Voltage	V_{GS} = 0 V, I_S = 2.6 A (Note 2)	–	0.7	1.1	V
		V_{GS} = 0 V, I_S = 44 A (Note 2)	–	0.8	1.2	V
t_{rr}	Reverse Recovery Time	I_F = 44 A, di/dt = 100 A/μs	–	65	104	ns
Q_{rr}	Reverse Recovery Charge		–	57	91	nC
t_{rr}	Reverse Recovery Time	I_F = 44 A, di/dt = 300 A/μs	–	49	79	ns
Q_{rr}	Reverse Recovery Charge		–	89	143	nC


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

THERMAL CHARACTERISTICS


Symbol	Characteristic	Value	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case (Top Source)	2.9	°C/W
$R_{\theta JC}$	Thermal Resistance, Junction to Case (Bottom Drain)	1.0	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1a)	38	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1b)	81	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1c)	27	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1d)	34	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1e)	16	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1f)	19	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1g)	26	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1h)	61	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1i)	16	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1j)	23	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1k)	11	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1l)	13	

NOTES:

1. $R_{\theta JA}$ is determined with the device mounted on a FR−4 board using a specified pad of 2 oz copper as shown below. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design.



a. 38°C/W when mounted on a 1 in^2 pad of 2 oz copper



b. 81°C/W when mounted on a minimum pad of 2 oz copper

c. Still air, 20.9 × 10.4 × 12.7 mm Aluminum Heat Sink, 1 in^2 pad of 2 oz copper
d. Still air, 20.9 × 10.4 × 12.7 mm Aluminum Heat Sink, minimum pad of 2 oz copper
e. Still air, 45.2 × 41.4 × 11.7 mm Aavid Thermalloy Part # 10−L41B−11 Heat Sink, 1 in^2 pad of 2 oz copper
f. Still air, 45.2 × 41.4 × 11.7 mm Aavid Thermalloy Part # 10−L41B−11 Heat Sink, minimum pad of 2 oz copper
g. 200FPM Airflow, No Heat Sink,1 in^2 pad of 2 oz copper
h. 200FPM Airflow, No Heat Sink, minimum pad of 2 oz copper
i. 200FPM Airflow, 20.9 × 10.4 × 12.7 mm Aluminum Heat Sink, 1 in^2 pad of 2 oz copper
j. 200FPM Airflow, 20.9 × 10.4 × 12.7 mm Aluminum Heat Sink, minimum pad of 2 oz copper
k. 200FPM Airflow, 45.2 × 41.4 × 11.7 mm Aavid Thermalloy Part # 10−L41B−11 Heat Sink, 1 in^2 pad of 2 oz copper
l. 200FPM Airflow, 45.2 × 41.4 × 11.7 mm Aavid Thermalloy Part # 10−L41B−11 Heat Sink, minimum pad of 2 oz copper

2. Pulse Test: Pulse Width < 300 μs, Duty cycle < 2.0%.
3. E_{AS} of 661 mJ is based on starting T_J = 25°C; N−ch: L = 3 mH, I_{AS} = 21 A, V_{DD} = 40 V, V_{GS} = 10 V. 100% test at L = 0.1 mH, I_{AS} = 66 A.
4. Pulse Id measured at 250 μs, refer to Figure 11 SOA graph for more details.

TYPICAL CHARACTERISTICS

(T_J = 25°C UNLESS OTHERWISE NOTED)




Figure 1. On−Region Characteristics




Figure 2. Normalized On−Resistance vs. Drain Current and Gate Voltage




Figure 3. Normalized On−Resistance vs. Junction Temperature




Figure 4. On−Resistance vs. Gate−to−Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Source−to−Drain Diode Forward Voltage vs. Source Current

TYPICAL CHARACTERISTICS (CONTINUED)

(T_J = 25°C UNLESS OTHERWISE NOTED)




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance vs. Drain−to−Source Voltage




Figure 9. Unclamped Inductive Switching Capability




Figure 10. Maximum Continuous Drain Current vs. Case Temperature




Figure 11. Forward Bias Safe Operating Area




Figure 12. Single Pulse Maximum Power Dissipation

TYPICAL CHARACTERISTICS (CONTINUED)

(T_J = 25°C UNLESS OTHERWISE NOTED)




Figure 13. Junction−to−Case Transient Thermal Response Curve

PACKAGE MARKING AND ORDERING INFOMRATION

PACKAGE MARKING AND ORDERING INFORMATION

Device	Device Marking	Package	Reel Size†	Tape Width	Quantity
FDMS8320LDC	2G	DUAL COOL 56	13″	12 mm	3000 Units

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


DUAL COOL and POWERTRENCH are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries.


MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS

ON Semiconductor®


DFN8 5x6.15, 1.27P, DUAL COOL
CASE 506EG
ISSUE D

DATE 25 AUG 2020






TOP VIEW




SIDE VIEW




DETAIL "A"
SCALE: 2:1

NOTES:


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. COPLANARITY APPLIES TO THE EXPOSED PADS AS WELL AS THE TERMINALS.
4. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.
5. SEATING PLANE IS DEFINED BY THE TERMINALS. "A1" IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.




FRONT VIEW



DETAIL "B"
SCALE: 2:1



BOTTOM VIEW




LAND PATTERN
RECOMMENDATION

*FOR ADDITIONAL INFORMATION ON OUR PB-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	0.85	0.90	0.95
A1	-	-	0.05
A2	-	-	0.05
b	0.31	0.41	0.51
b1	0.21	0.31	0.41
c	0.20	0.25	0.30
D	4.90	5.00	5.10
D1	4.80	4.90	5.00
D2	3.67	3.82	3.97
D3	2.60 REF		
D4	0.86 REF		
E	6.05	6.15	6.25
E1	5.70	5.80	5.90
E2	3.38	3.48	3.58
E3	3.30 REF		
E4	0.50 REF		
E5	0.34 REF		
E6	0.30 REF		
E7	0.52 REF		
e	1.27 BSC		
1/2e	0.635 BSC		
K	1.30	1.40	1.50
L	0.56	0.66	0.76
L1	0.52	0.62	0.72
Θ	0°	---	12°

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON84257G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**DFN8 5x6.15, 1.27P, DUAL COOL**	**PAGE 1 OF 1**

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2018

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Fairchild Semiconductor:

1N4148 1N4148TA 74ACQ573SCX 74VHC573MX DM7407MX FQPF3N80C ISL9V3040S3ST SI9936DY FDB8030L FDS2672 FDS6375 FDS8928A H11L1M ISL9V3040P3 KST42MTF MM74HC139N FCP190N60E FDP12N60NZ RFP12N10L SI9435DY FDS6990A FQP6N90C FSL126MR HLMP0504 KA278R12CYDTU MMBT3640