
Product data sheet
Miniature connectors

Product description	**M16 Male angled connector, Contacts: 4 (04-a), 4.0-6.0 mm, shieldable, solder, IP67, UL**
Area	**series 423**
Part no.	**99 5109 75 04**


Illustration



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	99 5109 75 04
Connector design	Male angled connector
Type standard	DIN EN 61076-2-106
Version	Connector pin angled
Connector locking system	screw
Termination	solder
Degree of protection	IP67
Cross-sectional area	max. 0.75 mm² / AWG 18
Cable outlet	4.0-6.0 mm
Twistability	90° (4 coding options)
Temperature range from/to	-30 °C / 95 °C
Mechanical operation	> 500 Mating cycles
Weight (g)	65.13
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	250 V
Rated impulse voltage	1500 V
Rated current	6.0 A
Insulation resistance	≥ 10^{10} Ω
Pollution degree	1
Overvoltage category	I
Insulating material group	III
EMC compliance	shieldable
Shield connection	Shielding ring

Product data sheet
Miniature connectors

Product description	**M16 Male angled connector, Contacts: 4 (04-a), 4.0-6.0 mm, shieldable, solder, IP67, UL**
Area	**series 423**
Part no.	**99 5109 75 04**

Material

Housing material	CuZn (Brass nickel plated)
Contact body material	PBT (UL94 V-0)
Contact material	CuZn (brass)
Contact plating	Ag (silver)
REACH SVHC	CAS 96-45-7 (Imidazolidine-2-thione) CAS 7439-92-1 (Lead)
SCIP number	3b43c27d-04cf-4786-8f1a-f7fe19091203

Authorization/approvals

Approvals	UL


Classifications

eCl@ss 11.1	27-44-01-02
ETIM 9.0	EC002635

Declarations of conformity

Low Voltage Directive	2014/35/EU (EN 60204-1:2018;EN 60529:1991)

Assembly instructions



Date: 07.08.2024

Product data sheet
Miniature connectors

Product description	**M16 Male angled connector, Contacts: 4 (04-a), 4.0-6.0 mm, shieldable, solder, IP67, UL**
Area	**series 423**
Part no.	**99 5109 75 04**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

The plug connector is not suitable for mains voltages Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Franz Binder:

09-0498-00-24 99-0609-00-04 99-9475-100-07 09-3442-92-05 14402780 79-3468-52-06 09-9749-20-03
09 0137 70 04 09-3481-679-08 09-3491-90-12 86 6919 0002 00703 99-0096-100-05 99-0491-12-12
99-4929-00-08 04 0722 000 09-0981-00-04 99 0975 102 03 99-3376-100-04 99-0401-10-02 99-3400-00-03
09 3463 00 06 09-0315-00-05 09-3105-86-03 79 5001 20 04 99-0072-100-02 99-0429-314-04
99-4905-00-03 99-9115-00-05 09-3432-500-04 99-0430-27-04