N-Channel and P-Channel Enhancement Mode Power MOSFET

Features

- N-Channel: 40V, 8A

  $R_{DS(ON)}$< 14 mΩ@ V_{GS} = 10V

  $R_{DS(ON)}$ <19 mΩ@ V_{GS} = 4.5V

- P-Channel: -40V, -7A

  $R_{DS(ON)}$< 29 mΩ@ V_{GS} = -10V

  $R_{DS(ON)}$ < 34 mΩ @ V_{GS} = -4.5V

General Features

- Advanced Trench Technology
- Provide Excellent RDS(ON) and Low Gate Charge
- Lead Free and Green Available

100% UIS TESTED!
100% ΔVds TESTED!

RoHS



SOP-8 Dual



Pin Assignment



Schematic diagram

Absolute Maximum Ratings (T_A=25℃unless otherwise noted)

Parameter		Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage		V_{DS}	40	-40	V
Gate-Source Voltage		V_{GS}	±20	±20	V
Continuous Drain Current	T_A=25℃	I_D	8	-7	A
	T_A=70℃		6	-5.5	
Pulsed Drain Current (Note 1)		I_{DM}	40	-30	A
Maximum Power Dissipation	T_A=25℃	P_D	2.0	2.0	W
Operating Junction and Storage Temperature Range		T_J,T_{STG}	-55 To 150	-55 To 150	℃

Thermal Characteristic

Thermal Resistance,Junction-to-Ambient (Note2)	$R_{\theta JA}$	N-Ch	62.5	℃/W
Thermal Resistance,Junction-to-Ambient (Note2)	$R_{\theta JA}$	P-Ch	62.5	℃/W

N-CH Electrical Characteristics (T_A=25℃unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V I_D=250μA	40	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=40V,V_{GS}=0V	-	-	1	μA
Gate-Body Leakage Current	I_{GSS}	V_{GS}=±20V,V_{DS}=0V	-	-	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=250μA	1		2.0	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=10V, I_D=8A	-		14	mΩ
		V_{GS}=4.5V, I_D=4A	-		19	mΩ
Forward Transconductance	g_{FS}	V_{DS}=5V,I_D=8A	33	-	-	S
Dynamic Characteristics (Note4)						
Input Capacitance	C_{lss}	V_{DS}=20V,V_{GS}=0V, F=1.0MHz	-	1110	-	PF
Output Capacitance	C_{oss}		-	114	-	PF
Reverse Transfer Capacitance	C_{rss}		-	109	-	PF
Switching Characteristics (Note 4)						
Turn-on Delay Time	$t_{d(on)}$	V_{DD}=20V, R_L=2.5Ω V_{GS}=10V,R_{GEN}=3Ω	-	5.5	-	nS
Turn-on Rise Time	t_r		-	14	-	nS
Turn-Off Delay Time	$t_{d(off)}$		-	24	-	nS
Turn-Off Fall Time	t_f		-	12	-	nS
Total Gate Charge	Q_g	V_{DS}=20V,I_D=8A, V_{GS}=10V	-	30	-	nC
Gate-Source Charge	Q_{gs}		-	5	-	nC
Gate-Drain Charge	Q_{gd}		-	7	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V_{SD}	V_{GS}=0V,I_S=8A	-	0.8	1.2	V

P-CH Electrical Characteristics (T_A=25℃unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V I_D=-250μA	-40	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-40V,V_{GS}=0V	-	-	-1	μA
Gate-Body Leakage Current	I_{GSS}	V_{GS}=±20V,V_{DS}=0V	-	-	±100	nA
On Characteristics (Note 3)						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS},I_D=-250μA	-1.0		-2.0	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=-10V, I_D=-7A	-		29	mΩ
		V_{GS}=-4.5V, I_D=-4A	-		34	mΩ
Forward Transconductance	g_{FS}	V_{DS}=-5V,I_D=-7A	20	-	-	S
Dynamic Characteristics (Note4)						
Input Capacitance	C_{lss}	V_{DS}=-20V,V_{GS}=0V, F=1.0MHz	-	1139	-	PF
Output Capacitance	C_{oss}		-	114	-	PF
Reverse Transfer Capacitance	C_{rss}		-	103	-	PF
Switching Characteristics (Note 4)						
Turn-on Delay Time	$t_{d(on)}$	V_{DD}=-20V, R_L=2.9Ω V_{GS}=-10V,R_{GEN}=6Ω	-	7.5	-	nS
Turn-on Rise Time	t_r		-	5.5	-	nS
Turn-Off Delay Time	$t_{d(off)}$		-	19	-	nS
Turn-Off Fall Time	t_f		-	7	-	nS
Total Gate Charge	Q_g	V_{DS}=-20V,I_D=-7A V_{GS}=-10V	-	22.5	-	nC
Gate-Source Charge	Q_{gs}		-	2.4	-	nC
Gate-Drain Charge	Q_{gd}		-	5.1	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage (Note 3)	V_{SD}	V_{GS}=0V,I_S=-7A	-	-	-1.2	V

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t ≤ 10 sec.
3. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production

N- Channel Typical Electrical and Thermal Characteristics (Curves)



Figure 1:Switching Test Circuit



Figure 2:Switching Waveforms



Figure 3 Output Characteristics



Figure 4 Transfer Characteristics



Figure 5 Drain-Source On-Resistance



Figure 6 Drain-Source On-Resistance



Vgs Gate-Source Voltage (V)

Figure7 Rdson vs Vgs



T_J-Junction Temperature(℃)

Figure 8 Power Dissipation



Qg Gate Charge (nC)

Figure 9 Gate Charge



Vds Drain-Source Voltage (V)

Figure 10 Source- Drain Diode Forward



Vds Drain-Source Voltage (V)

Figure 11 Capacitance vs Vds



Vds Drain-Source Voltage (V)

Figure 12 Safe Operation Area



Figure 13 Normalized Maximum Transient Thermal Impedance

P- Channel Typical Electrical and Thermal Characteristics (Curves)



Figure 1 Output Characteristics



Figure 4 Rdson-Junction Temperature



Figure 2 Transfer Characteristics



Figure 5 Gate Charge



Figure 3 Rdson- Drain Current



Figure 6 Source- Drain Diode Forward



Figure 7 Capacitance vs Vds



Figure 9 Power Dissipation



Figure 8 Safe Operation Area



Figure 10 $V_{GS(th)}$ vs Junction Temperature



Figure 11 Normalized Maximum Transient Thermal Impedance