CMP80N06P/CMB80N06P

N-Channel Enhancement Mode Field Effect Transistor

General Description

The 80N06P uses advanced power innovated design and silicon process technology to provide excellent RDS(ON). It can be used in a wide variety of applications.

Product Summary

BVDSS	RDSON	ID
60V	22mΩ	80A


Applications

- DC-DC converters
- LED power controller
- High current, high speed switching
- Motor control, Audio amplifiers


Features

- Fast switching
- Low On-Resistance
- 100% avalanche tested
- RoHS Compliant


TO-220/263 Pin Configuration



TO-220
(CMP80N06P)



TO-263
(CMB80N06P)



Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	60	V
V_{GS}	Gate-Source Voltage	±20	V
I_D@T_C=25℃	Continuous Drain Current	80	A
I_D@T_C=100℃	Continuous Drain Current	50	A
I_{DM}	Pulsed Drain Current[1]	320	A
EAS	Single Pulse Avalanche Energy[2]	450	mJ
P_D@T_C=25℃	Total Power Dissipation	145	W
T_{STG}	Storage Temperature Range	-55 to 150	℃
T_J	Operating Junction Temperature Range	-55 to 150	℃

Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction-ambient	---	62	℃/W
$R_{\theta JC}$	Thermal Resistance Junction-case	---	0.8	℃/W

Electrical Characteristics (T_J=25℃ , unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V , I_D=250uA	60	---	---	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V , I_D=25A	---	---	22	mΩ
$V_{GS(th)}$	Gate Threshold Voltage	V_{GS}=V_{DS} , I_D =250uA	2	---	4	V
I_{DSS}	Drain-Source Leakage Current	V_{DS}=60V , V_{GS}=0V	---	---	1	uA
		V_{DS}=48V , V_{GS}=0V@150℃	---	---	10	
I_{GSS}	Gate-Source Leakage Current	V_{GS} = ±20V , V_{DS}=0V	---	---	±100	nA
gfs	Forward Transconductance	V_{DS}=10V , I_D=22A	---	24	---	S
Q_g	Total Gate Charge	I_D=40A V_{DS} =30V V_{GS} =10 V	---	70	---	nC
Q_{gs}	Gate-Source Charge		---	22	---	
Q_{gd}	Gate-Drain Charge		---	34	---	
$T_{d(on)}$	Turn-On Delay Time	V_{DS} =30V I_D=40A R_G=25Ω	---	28	---	ns
T_r	Rise Time		---	120	---	
$T_{d(off)}$	Turn-Off Delay Time		---	70	---	
T_f	Fall Time		---	55	---	
C_{iss}	Input Capacitance	V_{DS}=25V , V_{GS}=0V , f=1MHz	---	2800	---	pF
C_{oss}	Output Capacitance		---	550	---	
C_{rss}	Reverse Transfer Capacitance		---	200	---	

Diode Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_S	Continuous Source Current	V_G=V_D=0V , Force Current	---	---	80	A
I_{SM}	Pulsed Source Current[1]		---	---	320	A
V_{SD}	Diode Forward Voltage	V_{GS}=0V , I_S=1 A, T_J=25℃	---	---	1.5	V

Note :
1.Repetitive rating; pulse width limited by max. junction temperature.

2.The test condition is V_{DD}=40V , V_{GS}=10V , L=1 mH , I_{AS}=30A

This product has been designed and qualified for the counsumer market.
Cmos assumes no liability for customers' product design or applications.
Cmos reserver the right to improve product design ,functions and reliability wihtout notice.