Push-in Y-fitting
QBY-10-32-UNF-5/32-U

Part number: 564684



General operating condition

Data sheet

Feature	Value
Size	Standard
Nominal width	2.489 mm
Type of seal on screwed plug	Sealing ring
Mounting position	Any
Design	Y-shape
Pack size	10
Structural design	Push-pull principle
Operating pressure for entire temperature range	0.095 MPa ... 1 MPa
Operating pressure for entire temperature range	0.95 bar ... 10 bar
Operating pressure for entire temperature range	13.775 psi ... 145 psi
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Information on operating and pilot media	Operation with oil lubrication possible
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
Ambient temperature	0 °C ... 60 °C
Max. tightening torque	1.5 Nm
Product weight	10.603 g
Type of mounting	External hexagon 7/16
Pneumatic connection 1	External thread 10-32 UNF-2A
Pneumatic connection 2	for pneumatic tubing outside diameter 5/32"
Ambient temperature Fahrenheit	32 °F ... 140 °F
Releasing ring color	Gray
Note on materials	RoHS-compliant
Housing material	Brass, nickel-plated PBT
Releasing ring material	POM
Material of tubing seal	NBR
Material of tube retaining claw	High-alloy stainless steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

NPQH-D-S14-Q8-P10 NPQH-T-G38-Q8-P10 VABM-L1-10HW-G18-4-GR VABM-L1-18S-G38-10 DFM-63-100-P-A-KF DSBC-40-50-D3-PPSA-N3 NPQH-D-Q14-E-P10 QSL-12 VABM-B10-25S-G38-6 153034 NPQP-D-R14-Q10-FD-P10 QS-G1/8-6-I QSLV-G1/4-6 SEA-3GS-M8-S SPTW-P16R-G14-A-M12 VABM-L1-14W-G14-4-GR DSBC-40-160-D3-PPSA-N3 DSBC-50-20-D3-PPSA-N3 NPQP-D-R38-Q10-FD-P10 QS-G3/8-12 QSL-1/4-4 NPQH-D-Q12-Q8-P10 QSLV-G1/2-12-I VABM-B10-20S-G14-6 VABM-B10-25S-G38-4-P3 DSBC-32-40-D3-PPVA-N3 DSBC-63-320-D3-PPVA-N3 DSBC-32-50-D3-PPVA-N3 HGL-1/8-B QSLV-G1/8-8