

## Description

The RZE002P02TL uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 2.5V. This device is suitable for use as a Battery protection or in other Switching application.




SOT-523
(SC-75(SOT-416))




P-Channel MOSFET

## General Features

$V_{DS}$ = -20V $I_D$ = -0.66A

$R_{DS(ON)}$ < 560 mΩ@ $V_{GS}$=-4.5V

$R_{DS(ON)}$ < 780 mΩ@ $V_{GS}$=-2.5V

ESD Rating: 1500V HBM

## Application

Battery protection

Load switch

Uninterruptible power supply

### Package Marking and Ordering Information

| Product ID | Pack | Brand | Qty(PCS) |
|---|---|---|---|
| RZE002P02TL | SOT-523(SC-75(SOT-416)) | HXY MOSFET | 3000 |

## Absolute Maximum Ratings ($T_A$=25℃unless otherwise noted)

| Symbol | Parameter | Limit | Unit |
|---|---|---|---|
| $V_{DS}$ | Drain-Source Voltage | -20 | V |
| $V_{GS}$ | Gate-Source Voltage | ±12 | V |
| $I_D$ | Drain Current-Continuous | -0.66 | A |
| $P_D$ | Maximum Power Dissipation | 150 | mW |
| $T_J$,$T_{STG}$ | Operating Junction and Storage Temperature Range | -55 To 150 | ℃ |
| $R_{\theta JA}$ | Thermal Resistance,Junction-to-Ambient (Note 2) | 833 | ℃/W |


## Electrical Characteristics ($T_J$=25℃, unless otherwise noted)


| Parameter | Symbol | Test conditions | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| **STATIC CHARACTERISTICE** | | | | | | |
| Drain-source breakdown voltage | $V_{(BR)DSS}$ | $V_{GS}$ = 0V, $I_D$ =-250μA | -20 | | | V |
| Zero gate voltage drain current | $I_{DSS}$ | $V_{DS}$ =-20V,$V_{GS}$ = 0V | | | -1 | μA |
| Gate-body leakage current | $I_{GSS}$ | $V_{GS}$ =±10V, $V_{DS}$ = 0V | | | ±10 | μA |
| Gate threshold voltage (note2) | $V_{GS(th)}$ | $V_{DS}$ =$V_{GS}$, $I_D$ =-250μA | -0.4 | -0.7 | -1.0 | V |
| Drain-source on-resistance (note2) | $R_{DS(on)}$ | $V_{GS}$ =-4.5V, $I_D$ =-0.5A | | | 0.56 | Ω |
| | | $V_{GS}$ =-2.5V, $I_D$ =-0.2A | | | 0.78 | Ω |
| Maximum Continuous Drain to Source Diode Forward Current | $I_S$ | -- | | | -0.6 | A |
| Maximum Pulsed Drain to Source Diode Forward Current | $I_{SM}$ | -- | | | -1.2 | A |
| Diode forward voltage | $V_{SD}$ | $I_S$=-0.5A, $V_{GS}$ = 0V | | | -1.2 | V |
| **DYNAMIC CHARACTERISTICS** (note4) | | | | | | |
| Input capacitance | $C_{iss}$ | $V_{DS}$ =-16V,$V_{GS}$ =0V, f =1MHz | | 115 | | pF |
| Output capacitance | $C_{oss}$ | | | 15 | | pF |
| Reverse transfer capacitance | $C_{rss}$ | | | 9 | | pF |
| **SWITCHING CHARACTERISTICS** (note4) | | | | | | |
| Turn-on delay time (note3) | $t_{d(on)}$ | $V_{GS}$=-4.5V,$V_{DS}$=-10V, $I_D$=-200mA,$R_{GEN}$=10Ω | | 9 | | nS |
| Turn-on rise time (note3) | $t_r$ | | | 6 | | nS |
| Turn-off delay time (note3) | $t_{d(off)}$ | | | 33 | | nS |
| Turn-off fall time (note3) | $t_f$ | | | 22 | | nS |


Notes:

1. Surface mounted on FR4 board using the minimum recommended pad size.
2. Pulse Test : Pulse Width=300μs, Duty Cycle=2%.
3. Switching characteristics are independent of operating junction temperatures.
4. Guaranteed by design, not subject to producting.

## SOT-523(SC-89(SOT-416)) Package Information





| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|---|---|---|---|---|
| | Min. | Max. | Min. | Max. |
| A | 0.700 | 0.900 | 0.028 | 0.035 |
| A1 | 0.000 | 0.100 | 0.000 | 0.004 |
| A2 | 0.700 | 0.800 | 0.028 | 0.031 |
| b1 | 0.150 | 0.250 | 0.006 | 0.010 |
| b2 | 0.250 | 0.350 | 0.010 | 0.014 |
| c | 0.100 | 0.200 | 0.004 | 0.008 |
| D | 1.500 | 1.700 | 0.059 | 0.067 |
| E | 0.700 | 0.900 | 0.028 | 0.035 |
| E1 | 1.450 | 1.750 | 0.057 | 0.069 |
| e | 0.500 TYP. | | 0.020 TYP. | |
| e1 | 0.900 | 1.100 | 0.035 | 0.043 |
| L | 0.400 REF. | | 0.016 REF. | |
| L1 | 0.260 | 0.460 | 0.010 | 0.018 |
| θ | 0° | 8° | 0° | 8° |

## SOT-523 Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

## Attention

■ Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

■ HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

■ Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer’s products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer’s products or equipment.

■ HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could
give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

■ Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## HXY MOSFET:

TPSMB100CA-VR HC4D20120A HESDNC5VB1AF-B MMBT3904T SS10100 SS510C BZT52C3V3S DTC143ZE HAD8542ARZ HMCP602-I/SN HT7540-1 HOPA2340UA HT7150 MAX487ESA HXY8205ES IRLML6246PBF P6SMB33CA P6SMB36CA SD15C SS1045 TPSMB28A-VR SQJA04EP-T1_BE3 SS5150B BZT52C13 HC3D10170A P6SMB200A HXY2101EI PESD5V0S1BB US2M HXY2300MI