


Inductive sensor

NMB1,5-8GM35-E2-C-FE-150MM-V3

- Stainless steel sensing face
- 1.5 mm flush
- 3-wire DC
- Weld field immune
- Weld slag resistant coating
- Ferrous targets

Dimensions



Technical Data


General specifications		
Switching function		Normally open (NO)
Output type		PNP
Rated operating distance	s_n	1.5 mm
Installation		flush in mild steel
Output polarity		DC
Assured operating distance	s_a	0 ... 1.215 mm

Release date: 2024-01-16 Date of issue: 2024-01-16 Filename: 909310_eng.pdf

Technical Data


Actuating element		Ferrous targets
Reduction factor r_{Al}		0
Reduction factor r_{Cu}		0
Reduction factor r_{304}		0.4 - 0.7
Reduction factor r_{St37}		1
Reduction factor r_{Brass}		0
Output type		3-wire
Nominal ratings		
Operating voltage	U_B	10 ... 30 V DC
Switching frequency	f	0 ... 5 Hz
Hysteresis	H	5 ... 15 typ. 10 %
Reverse polarity protection		reverse polarity protected
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 2 V
Operating current	I_L	0 ... 100 mA
Current consumption		≤ 10 mA
Off-state current	I_r	≤ 10 µA
Switching state indicator		LED, red
Mag. Field strength, AC fields		250 mT
Mag. Field strength, DC fields		250 mT
Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		-25 ... 75 °C (-13 ... 167 °F)
Mechanical specifications		
Connection type		Cable connector M8 x 1 , 3-pin with PVC Cable, 150 mm
Core cross section		0.14 mm²
Housing material		Xylan coated - Stainless steel 1.4305 / AISI 303
Sensing face		Xylan coated - Stainless steel 1.4305 / AISI 303
Degree of protection		IP67
Dimensions		
Length		35 mm
Diameter		8 mm

Connection



Release date: 2024-01-16 Date of issue: 2024-01-16 Filename: 909310_eng.pdf

Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
3	BU	(blue)
4	BK	(black)

Release date: 2024-01-16 Date of issue: 2024-01-16 Filename: 909310_eng.pdf

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

PEPPERL+FUCHS:

MH4-2057 NBB1-4GM22-E2 NBB2-12GM50-E2 GLV30-8-2500/47/73C KLR-C02-2,2-2,0-K70 NBB2-8GM40-E0-V1 NBB5-18GM50-E2 S1SD-1AI-1U.1 UB2000-F42-E6-V15 WCS3-MH1 BF18 NBB0.8-4M25-E0 NBB0.8-5GM25-E2 OBR12M-R100-2EP-IO-V31-L CCN15-30GS60-E2-V1 NBB5-18GM50-A0 OBR5000-18GK40A-E2 134143 34441 OBD450-18GK40A-E2 OQT150-R100-2EP-IO-V31-L 114642 NBB8-18GM50-E0 UB800-18GM40-I-V1 UBE800-F77-SE2-V31 24772 NBB2-12GM50-A2-V1 NBB4-12GM50-A2-V1 OBR2500-12GM40-E5 OQT150-R101-2EP-IO-V31