Current refinements (click ☒ to remove) Search Tips

☒ Region ▸ USA ☒ Product Family ▸ HSTTA Heat Shrink ☒ Text Search: 'HSTTA19-48-Q'

Your search criteria matched only one product, shown below.



Dual Wall Polyolefin DAMPSHRINK™ Heat Shrink Tubing in 4 ft Pieces

- For damp locations
- Flexible tubing with an adhesive inner wall which seals and protects components from moisture and corrosion
- The 3:1 shrink ratio is a benefit when working with connector-to-cable transitions
- Material Type: Polyolefin CrossLinked with adhesive
- Shrink Ratio: 3:1
- Temperature Range:-67°F to 230°F (-55°C to 110°C)
- Flammability: Outer wall flame retardant
- Voltage Rating: 600V
- Mil Spec: AMS-DTL-23053/4 Class 3

Part Number:	HSTTA19-48-Q
RoHS Compliancy Status:	Compliant
Part Description:	Dual Wall Adhesive Lined Thin Wall Heat Shrink
Material:	Polyolefin cross-linked with adhesive.
Color:	Black
Military Specification:	AMS-DTL-23053/4 Class 3
Length (ft.):	4
Flammability Rating:	Outer Wall Flame Retardant
Max. Recovered I.D. (In.):	.062
Max. Recovered I.D. (mm):	1.6
Min. Expanded I.D. (In.):	.187
Min. Expanded I.D. (mm):	4.8
Nominal Diameter (In.):	3/16
Nominal Diameter (mm):	4.8
Nominal Recovered Wall Thickness (In.):	.040
Nominal Recovered Wall Thickness (mm)	1.0
Shrink Ratio:	3:1
Temperature Range:	-67°F to 230°F (-55°C to 110°C)
Min. Order UOM:	PC
Min. Order Qty.:	25
BOM Qty. (# of Pkgs.)	0
Add to My Catalog	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

View Content Details

Evaluate	Design a Solution	Install & Maintain
		Installation Instructions: Pan-Shrink Heat Shrink- In001 pdf

Copyright © 1995-2007, PANDUIT CORP. All rights reserved.