Automotive & Industrial Grade 32.768kHz Continues Voltage SMD Crystal XO

ASAKDVAIG series

Request Samples | Check Inventory

ESD Sensitive

2.0 x 1.6 x 0.8 mm

RoHS/RoHS II Compliant

MSL Level = 1

Features

- Continuous V_{DD} operation from 1.62 V ~ 3.63 V
- Optimized for low current consumption
- Output Enable/Start & Disable/Stop function
- Output waveform CMOS/LVCMOS compatible
- Hermetically seam-sealed ceramic package
- AEC-Q200 Qualified
- Automotive Grade 1: -40°C to +125°C
- TS16949 Production Line Certified
- PPAP Available Upon Request

Applications

- Infotainment Systems
- Keyless Entry & Startup
- GPS & Navigation
- Comfort control
- ADAS (Advanced Driver Assistance Systems)
- Vehicle to Vehicle Communication
- LiDAR (Light Detection and Ranging)
- In-vehicle Networking
- Powertrain & Drive Control
- Power Control & Conversion
- Industrial Control & Automation

Electrical Specifications

Parameters		Min.	Typ.	Max.	Units	Notes
Frequency			32.768		kHz	
Operating Temperature Range		-40.0		+125	°C	See options
Storage Temperature Range		-55.0		+125	°C	
Overall Frequency Stability [Note 1]		-100		+100	ppm	See options
Supply Voltage (Vdd)		+1.62		+3.63	V	
Tri-state function [Note 2]		"1" (VIH≥0.7*Vdd) or Open: Oscillation; "0" (VIL<0.3*Vdd): No Oscillation/Hi Z			V	
Output Load				15	pF	CMOS
Output Voltage	V_{OH}	0.9*Vdd			V	
	V_{OL}			0.1*Vdd		
Aging 1 year @25°C± 3°C		-3.0		+3.0	ppm	
Aging 5 years @25°C± 3°C		-5.0		+5.0	ppm	
Symmetry @ ½ Vdd		45	50	55	%	
Start-up Time				10	ms	
Rise and Fall Time (Tr/Tf) @10%Vdd-90%Vdd, 15pF load			10	50	ns	
Disable Current				5	µA	
Supply Current (Idd) @25°C± 3°C	Vdd = 3.3V		18	30	µA	No Load
	Vdd = 2.5V		19	30	µA	No Load
	Vdd = 1.8V		20	30	µA	No Load

Note 1: Overall frequency stability includes initial frequency tolerance @25°C± 3°C and stability over the operating temperature range.

Note 2: Do not leave pin 1 ($\overline{INH}$) floating. If pin 1 ($\overline{INH}$) is not utilized for toggling, it must be tied to Vdd (logic 1).

Part Identification

ASAKDVAIG-32.768kHz- [ ] [ ] - [ ]

Operating Temp.
L: -40°C ~ +85°C
M: -40°C ~ +105°C
K: -40°C ~ +125°C

Overall Freq. Stability
C: ± 50 ppm
Q: ± 100 ppm

Packaging
Blank: Bulk
T3: 3k pcs / reel

ABRACON

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-22-24

ABRACON IS ISO9001-2015 CERTIFIED

Automotive & Industrial Grade 32.768kHz Continues Voltage SMD Crystal XO


ASAKDVAIG series

Request Samples | Check Inventory


ESD Sensitive | Pb

2.0 x 1.6 x 0.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Typical Current Consumption (Idd) vs. Supply Voltage (Vdd) Characteristics [@ 25°C± 3°C, No Load]



Typical Frequency vs. Supply Voltage (Vdd) Characteristics [@ 25°C± 3°C, Normalized to Vdd=3.3Vdc]



ABRACON

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-22-24

ABRACON IS ISO9001-2015 CERTIFIED


Automotive & Industrial Grade 32.768kHz Continues Voltage SMD Crystal XO

ASAKDVAIG series


Request Samples | Check Inventory | ESD Sensitive | Pb

2.0 x 1.6 x 0.8 mm
RoHS/RoHS II Compliant
MSL Level = 1


Mechanical Dimensions



TOP VIEW




SIDE VIEW



BOTTOM VIEW

Recommended Land Pattern



Pin #	Function
1	$\overline{INH}$
2	GND
3	Output
4	Vdd

$\overline{INH}$ Function	
#1	#3 (Output)
Open	Active
"H" Level	Active
"L" Level	High Z (No Oscillation)

Note 3:
-Do not leave Pin 1 ($\overline{INH}$) floating
-If Pin 1 ($\overline{INH}$) is not utilized for toggling, it must be tied to Vdd (logic 1)

Note 4:
Recommended to use approximately 0.01µF bypass capacitor between PIN 2 and PIN 4

Dimensions: inches (mm)

ABRACON

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-22-24

ABRACON IS ISO9001-2015 CERTIFIED

Automotive & Industrial Grade 32.768kHz Continues Voltage SMD Crystal XO

ASAKDVAIG series

Request Samples | Check Inventory

ESD Sensitive | Pb

2.0 x 1.6 x 0.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Reflow Profile [JDEC J-STD-020]




Table 1

SnPb Eutectic Process Classification Temperatures (T_c)		
Package Thickness	**Volume mm³ <350**	**Volume mm³ ≥350**
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2

Pb-Free Process Classification Temperatures (T_c)			
Package Thickness	**Volume mm³ <350**	**Volume mm³ 350-2000**	**Volume mm³ >2000**
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm - 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat / soak		
Temperature minimum (T_{smin})	100°C	150°C
Temperature maximum (T_{smax})	150°C	200°C
Time (T_{smin} to T_{smax}) (t_s)	60 - 120 sec.	60 - 120 sec.
Average ramp-up rate (T_{smax} to T_P)	3°C/sec. max	3°C/sec. max
Liquidous temperature (T_L)	183°C	217°C
Time at liquidous (t_L)	60 - 150 sec.	60 - 150 sec.
Peak package body temperature (T_P)*	**see Table 1**	**see Table 2**
Time (t_p)** within 5°C of the specified classification temperature (T_C)	20 sec.	30 sec.
Ramp-down rate (T_p to T_{smax})	6°C/sec. max	6°C/sec. max
Time 25°C to peak temperature	6 min. max	8 min. max

*Tolerance for peak profile temperature (T_P) is defined as a supplier minimum and a user maximum.

**Tolerance for time at peak profile temperature (t_p) is defined as supplier minimum and a user maximum.

ABRACON

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-22-24

ABRACON IS ISO9001-2015 CERTIFIED

Automotive & Industrial Grade 32.768kHz Continues Voltage SMD Crystal XO

ASAKDVAIG series

Request Samples | Check Inventory

ESD Sensitive


2.0 x 1.6 x 0.8 mm


RoHS/RoHS II Compliant

MSL Level = 1

Packaging

T3: 3,000pcs/reel





Dimensions: mm

ATTENTION: Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.

ABRACON

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-22-24

ABRACON IS ISO9001-2015 CERTIFIED

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

ABRACON:

AISC-1008F-100G-T AMDLA4010S-2R2MT ABLSG-24.000MHz-D-2-Y-T AMPMGFB-25.0000T
ATX-11-F-27.000MHZ-F05-T ASEMB-100.000MHZ-LY-T ASPIAIG-Q5030-1R0M-T ABM8-27.000MHZ-B2-T
ABM8G-24.000MHz-4-Y-T3 ASV-125.000MHZ-EC-T ABLS-16.000MHZ-D4-T AMPLA5030Q-4R7MT
ASE3-25.000MHz-E-K-T ASPIAIG-F1040-R36M-T FC5BAEEMM8.0-T1 FT5HNBPK25.0-T1
ABM8AIG-24.000MHZ-12-2Z-T3 ACHL-25.000MHZ-EK ACML-0402HC-301-T AMPMAFB-27.0000T
ASCO-50.000MHz-E-K-T3 ASDMB-8.000MHZ-LC-T ASPI-F1010-4R7M-T ATCA-07-101M-H
ABM8G-16.000MHz-4-Y-T3 ABM8-24.000MHZ-D4Y-T ABMM2-10.000MHZ-E2-T
ABM11W-16.0000MHZ-8-K1Z-T3 ASPI-M3015-2R2M-T ASPIAIG-Q1060-1R0M-T