RH100-40.000-9-F-1010-EXT-TR

SPECIFICATIONS

PARAMETER	VALUE
NOMINAL FREQUENCY	40.000 MHz
MODE OF OSCILLATION	Fundamental
FREQUENCY TOLERANCE AT 25°C	±10 ppm max
FREQUENCY STABILITY OVER TEMPERATURE	±10 ppm max
OPERATING TEMPERATURE RANGE	-40°C to +85°C
STORAGE TEMPERATURE RANGE	-40°C to +85°C
AGING	±3 ppm per year max
LOAD CAPACITANCE	9 pF
EQUIVALENT SERIES RESISTANCE	60 Ω max
SHUNT CAPACITANCE	5 pF max
DRIVE LEVEL	300 µW typ, 500 µW max







Photo is not actual part


MECHANICAL SPECIFICATION





PIN CONNECTION - Top View






SOLDER PATTERN

Scale none - Dimensions in mm / inch

CARRIER TAPE DIMENSIONS




NOTE: REFER TO EIA-481 FOR DIMENSIONS

PACKAGING

178 mm REEL DIAMETER
8 mm TAPE WIDTH, 4 mm PITCH
QUANTITY: 3000 PIECES PER REEL

IN ACCORDANCE WITH EIA-481

REFLOW PROFILE



Reflow profile		
Temperature Min Preheat	T_{SMIN}	125°C
Temperature Max Preheat	T_{SMAX}	150°C
Time (T_{SMIN} to T_{SMAX})	t_S	60-180 sec
Temperature	T_L	217°C
Peak Temperature	T_P	260°C
Ramp-up rate	R_{UP}	3°C/sec max
Ramp-down rate	R_{DOWN}	6°C/sec max
Time within 5°C of Peak Temperature	t_P	10 sec
Time t[25°C] to Peak Temperature	t[25°C] to Peak	480 sec
Time	t_L	60-150 sec.

ENVIRONMENTAL

PARAMETER	VALUE
MOISTURE SENSITIVITY LEVEL	1
RoHS-2	6/6 Compliant & Lead Free
REACH SVHC	Compliant
HALOGEN-FREE	Compliant
ESD CLASSIFICATION LEVEL	N/A
TERMINATION FINISH	Au

MARKING

R40.00
xx9Eyw

x – Internal Production ID code
y – Year code
w – Week code

YEAR CODE	
Year	**Code**
2011	1
2012	2
2013	3
2014	4
2015	5
2016	6
2017	7
2018	8
2019	9

ALPHA WEEK CODE TABLE					
Week	**Code**	**Week**	**Code**	**Week**	**Code**
1	a	19	s	37	K
2	b	20	t	38	L
3	c	21	u	39	M
4	d	22	v	40	N
5	e	23	w	41	O
6	f	24	x	42	P
7	g	25	y	43	Q
8	h	26	z	44	R
9	i	27	A	45	S
10	j	28	B	46	T
11	k	29	C	47	U
12	l	30	D	48	V
13	m	31	E	49	W
14	n	32	F	50	X
15	o	33	G	51	Y
16	p	34	H	52	Z
17	q	35	I		
18	r	36	J		

APPROVAL

DRAWN BY	KJackson, December 22, 2016
APPROVED BY	JIvens, December 22,2016
REVISION	A, Initial Release

Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2016, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Raltron Electronics:

TT-SMDC-3.6864-S-TR AS-20.000-20 AS-27.000-20-F AS-3.6864-18-SMD
H130A-25.000-18-F-2030-EXT-TR H130B-12.000-18-3030-TR RH100-40.000-18-F-2030-EXT-TR-NS1
RH100-48.000-8-F-1015-EXT-TR CO4305-20.000-EXT-T-TR CO4605-125.000-EXT-T-TR
CO4605-66.000-EXT-T-TR R2520-16.384-10-2030-EXT-TR-NS1 RH100-20.000-18-2020-TR
AS-20.000-20-SMD-TR RH100-16.000-16-5050-TR RH100-48.000-10-F-1015-EXT-TR
RH100-16.384-16-2020-EXT-TR-NS1 RTXE-104ED333-C-12.800-TR H130A-24.000-18-2030-EXT-TR
H130B-16.000-18-3030-EXT-TR CL2520-156.250-1.8-20-X-T-TR-N1 R2016-48.000-7-F-1020-TR-NS1
AS-10.000-18-SMD AS-14.7456-20-SMD-TR H130A-8.000-8-2030-TR RH100-40.000-10-F-2020-EXT-TR
AS-24.000-18 AS-8.000-18 CO4305-10.000-EXT-T-TR RH100-12.000-18-2020-TR