TECH PUBLIC
台舟电子

TPESD0594PA

4-Lines Uni-directional Channels ESD protection

WWW.TECHPUBLIC.COM

Features

- 4 Uni-directional Channels ESD protection
- Typically Used at High Speed Ports
- Low operating voltage: 5V
- Low Channel Input Capacitance of 0.4pF Typical for I/Os (Typ)
- –IEC 61000-4-2 (ESD) immunity test
  Air discharge: ±30kV
  Contact discharge: ±30kV

–IEC61000-4-4 (EFT) 40A (5/50ns)

- Totally Lead-Free & Fully RoHS Compliant
- Halogen and Antimony Free. “Green” Device


Mechanical Characteristics


- Package: DFN2510-10
- Lead Finish: Matte Tin
- Case Material: “Green” Molding Compound
- Terminal Connections: See Diagram Below
- -IEC 61000-4-2 (ESD) immunity test

Applications

- USB 3.1 & 3.2 and MDDI ports
- PCI express and Serial SATA
- Ports Notebook Computers
- Tablets

Dimensions and Pin Configuration





DFN2510-10

WWW.SOT23.COM.TW


Absolute Maximum Ratings(Tamb=25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20μs)	Ppp	84	W
IEC 61000−4−2 Spec Current at 60 ns (A)	Ipp	8	A
ESD per IEC 61000−4−2 (Air) ESD per IEC 61000−4−2 (Contact)	VESD	±30 ±30	KV
Operating Temperature Range	TJ	−55 to +125	°C
Storage Temperature Range	Tstg	−55 to +150	°C

Electrical Characteristics (TA=25°C unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM	--	--	5	V	
Breakdown Voltage	VBR	6	--	9.5	V	IT= 1mA
Reverse Leakage Current	IR	--	--	0.1	uA	VRWM=5V
Clamping Voltage	VC	--	5.5	7	V	Ipp=1A(8x 20us pulse)
Clamping Voltage	VC	--	8.5	10.5	V	Ipp=8A(8x 20us pulse)
Junction Capacitance	CJ	--	0.4	0.65	pF	VR = 0V, f = 1MHz, Any I/O pin to GND
Junction Capacitance	CJ	--	0.2	--	pF	VR = 0V, f = 1MHz, Between any I/O pin

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Maximum Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_F	Forward Current
V_F	Forward Voltage @ I_F
P_{pk}	Peak Power Dissipation
C	Capacitance @ V_R = 0 and f = 1.0 MHz



Uni−Directional TVS

Characteristic Curves

Fig1. 8/20μs Pulse Waveform




Fig2. ESD Pulse Waveform (according to IEC 61000-4-2)






Fig3. Power Derating Curve




Package Outline Dimensions (unit: mm)

DFN2510-10



Mounting Pad Layout (unit: mm)



Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TECH PUBLIC:

BV15C IRFR2405TRPBF-TP TPESD5311N QM3003J-TP SN7002W TPADM809SAKSZ DMP6350S TPDMG6602SVT TPS3809L30DBVR-TP TPSPX3819M5-L-3-3 TPZXMP3A13FTA SI3932DV TPADM809LAKSZ TPFMMT493 TPZVN3320FTA LTH7 TPB1A30-123 TPESD0402G08V TPS7B6950DBVR-TP TPWSB5557Z DDTA143ZCA TPAPX809S-31SA TPESD0504S6-A TPGC12C-1 FDC6301N-TP FDMS7670AS-TP TPB05A40-323 BSN20W ESD5B5.0ST1G-P TPD1213A-02SM