Product data sheet


Automation technology - Sensors and actuators

Product description	**M8 Female angled connector, Contacts: 3, 3.5-5.0 mm, shieldable, solder, IP67, UL**
Area	**series 768**
Part no.	**99 3364 00 03**


Illustration



Scale drawing



Contact arrangement (Plug-in side)



You can find the component part drawing and assembly instructions on the next page.

Technical data

General features

Part no.	99 3364 00 03
Connector design	Female angled connector
Type standard	DIN EN 61076-2-104
Version	Connector socket angled
Connector locking system	screw
Termination	solder
Degree of protection	IP67
Cross-sectional area	0.25 mm² / AWG 24
Cable outlet	3.5-5.0 mm
Twistability	90° (4 coding options)
Temperature range from/to	-40 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	25.08
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	30 V
Rated impulse voltage	1500 V
Rated current	4.0 A
Pollution degree	3
Overvoltage category	III
Insulating material group	III
EMC compliance	shieldable

Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Female angled connector, Contacts: 3, 3.5-5.0 mm, shieldable, solder, IP67, UL**
Area	**series 768**
Part no.	**99 3364 00 03**

Shield connection	Shielding ring

Material

Contact body material	PA
Contact material	CuSn (bronze)
Contact plating	Au (gold)
Locking material	CuZn (brass)
REACH SVHC	CAS 96-45-7 (Imidazolidine-2-thione) CAS 7439-92-1 (Lead)
SCIP number	a5c6f0e9-58f6-4349-8cf8-3634af413077

Authorization/approvals

Approvals	UL


Classifications

eCl@ss 11.1	27-44-01-02
ETIM 9.0	EC002635

Declarations of conformity

Low Voltage Directive	2014/35/EU (EN 60204-1:2018;EN 60529:1991)

Assembly instructions




1. *Bead parts on cable.*
2. *Strip, shorten, widen shield and lay around shielding ring.*
3. *Bead single wires through housing, mount shieldingring, sealing ring and pinch ring. Slightly tighten pressing screw to fix the cable. Bead insulating tube, solder single wires and mount insulting tube.*
4. *Screw male or female contact carrier to housing and tighten pressing screw.*
5. *Angled version: tighten locking screw.*

Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Female angled connector, Contacts: 3, 3.5-5.0 mm, shieldable, solder, IP67, UL**
Area	**series 768**
Part no.	**99 3364 00 03**

Component part drawing



Date: 27.07.2024

Product data sheet

Automation technology - Sensors and actuators

Product description	**M8 Female angled connector, Contacts: 3, 3.5-5.0 mm, shieldable, solder, IP67, UL**
Area	**series 768**
Part no.	**99 3364 00 03**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

The plug connector is not suitable for mains voltages Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 50 cNm).

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Franz Binder:

09-3105-86-03 79 5001 20 04 99-0401-10-02 99-4905-00-03 99-9115-00-05 09-3432-500-04 09-3442-92-05 09-3481-679-08 99-0096-100-05 09 3463 00 06 99-0429-314-04 99-0430-27-04 99-3400-00-03 99-4929-00-08 99-0072-100-02 99-0491-12-12 99-3376-100-04 09 0137 70 04 09-3491-90-12 14402780 99 0975 102 03 99-9475-100-07 09-0315-00-05 09-0498-00-24 86 6919 0002 00703 99-0609-00-04 04 0722 000 09-0981-00-04 09-9749-20-03 79-3468-52-06