








GT-TC133X-HXXX-LX


G-SWITCH

Operating Force
B=350gf


Switch Height(mm)
H064=6.4mm


Switch lifetime (Force)
L1=100,000 Cycles





P.C.B LAND DIMENSION





CIRCUIT

Pb Process Capable | RoHS Compliant 2002/95/EC | HALOGEN Compliant Halogen Free

G-Switch Specification:
Operating temperature range -40 to+160
Rating 50mA.12V DC
Insulation resistance: 100MΩ min.100V DC
Dielectric strength 250V AC for 1 min
Contact resistance: 100m Ω max.
Travel:1.0±0.2mm
WATER RESISTANCE: IPX7

品赞科技 G-Switch®

G-Switch Electronic (HongKong) CO.,Ltd.

Unless otherwise specified, Tolerance:	
X.	±0.30
X.x	±0.20
X.xx	±0.15
X.xxx	±0.10
Angles	±3°

DESIGN FengFengChen	DATE 2019.05.29	Molde code:	
CHECKED	DATE	GT-TC133X-HXXX-LX	
APPROVED	DATE		
http://www.dg-switch.com		REV.: X1	SCALE: 4:1	UNIT: mm
TEL:0769-82388879		SIZE: A4	SHEET: 1/1	

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

G-Switch:

GT-BTP30007-0240B-019B GT-B0403FSV19-50B1101 GT-B0803MSV20-10B0401
GT-BTP16006-0180B-014B GT-BTP25004-0400A-010A GT-BTP30004-0350B-019B SS-23H02-G080
ST-0275S00-082-182 GT-TC193A-H0675-L1 GT-USB-6017 GT-USB-7019D GT-USB-7084B
GT-BTP30007-0350B-019B GT-BTP30006-0650B-015A GT-TC025D-H0065-L1 GT-USB-7012D
GT-BTP30007-0720B-015A GT-BTP30006-0500B-015A GT-USB-2201 GT-USB-7010EN
GT-B0803MSV20-60B0401 GT-BTR20008-0460A-004A GT-TC155A-H0060-L50 GT-TCB73B-H090-L1
GT-F0502SR20-04SMT01 GT-BTP30004-0720B-015A GT-TC074A-H050-L1 GT-TC079A-H0040-L1
GT-USB-7010H GT-USB-7093B