Harvatek 3.0mm Round LED LAMP with Holder

HV-32312/260/SYGSUB-U1930

DISCLAIMER

HARVATEK reserves the right to make changes without further notice to any products herein to improve reliability, function or design. HARVATEK does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

LIFE SUPPORT POLICY

HARVATEK's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of HARVATEK or HARVATEK INTERNATIONAL. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.

2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Compliance and Certification

ISO9002, QS9000 and ISO14001 Certified
RoHS Compliant



Orderable Information


H V - 32312 / 260 / SYGSUB - U1930

Series Name	Color Code	Remark
HV : **HARVATEK**	**32312:Array 2 Lamp** **260:** **3.0mm Round LED LAMP.** **SYGSUB:** **AlGaInP 570nm Green Chip.** **InGaN 470nm Blue Chip.**	**U1930:** **Customer Product Code**

Features:

- Stable Color
- Popular 3.0mm through hole package.
- Green diffused lens and Blue Diffused Lens.

Package Dimensions:



Notes:

1.All dimensions are millimeters.

2.Tolerance is +/-0.25mm unless otherwise noted.

3.Specifications are subject to change without notice.

Absolute Maximum Ratings at Ta=25℃

Parameter	Symbol		Rating	Unit
Forward Current	I_F		30	mA
Operating Temperature	Topr		-40to+85	℃
Storage Temperature	Tstg		-40to+85	℃
Soldering Temperature*1	Tsol		260±5	℃
Power Dissipation	P_d	G	75	mW
		B	100	
Reverse Voltage	V_R		5	V
Peak Forward Current*2	I_{FP}	G	75	mA
		B	100	

*1:Soldering time ≦ 5 seconds. *2: Pulse Width≦ 100μs and Duty≦ 1% .

Electrical and Optical Characteristic

Parameter	Symbol	Condition		Min.	Typ.	Max.	Unit
Forward Voltage	V_F	I_F=20mA	G	/	2.0	2.4	V
			B	/	3.0	3.4	
Reverse Current	I_R	V_R= 5 V		/	/	10	μA
Luminous Intensity	I_V	I_F=20mA	G	25	100	/	mcd
			B	400	1200	/	
Viewing Angle	$2\theta_{1/2}$	I_F=20mA		/	30	/	deg
Peak Wavelength	λρ	I_F=20mA	G	/	575	/	nm
			B	/	465	/	
Dominant Wavelength	λ_d	I_F=20mA	G	/	570	/	nm
			B	/	470	/	
Spectrum Radiation Bandwidth	Δλ	I_F=20mA	G	/	25	/	nm
			B	/	20	/	

Notes:

θ1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.

Specifications for Bin Grading:(G)

Iv（mcd）		
Grade	Min.	Max.
N	25	50
P	40	80
Q	63	125
R	100	200

λd（nm）		
Grade	Min.	Max.
5	566	569
6	568	571
7	570	573
8	572	575
9	574	577

Notes:

1.Luminous intensity:+/-15%.

2.Wavelength: +/-1nm.

Specifications for Bin Grading:(B)

Iv（mcd）		
Grade	Min.	Max.
U	400	800
V	630	1250
W	1000	2000
X	1600	3200


λd（nm）		
Grade	Min.	Max.
2	463.5	466.5
3	465.5	468.5
4	467.5	470.5
5	469.5	472.5
6	471.5	474.5
7	473.5	476.5

Notes:


1.Luminous intensity:+/-15%.

2.Wavelength: +/-1nm.

Typical Electro-Optical Characteristics Curve(G)



Typical Electro-Optical Characteristics Curve(B)




Soldering condition

1. Careful attention should be paid during soldering. When soldering, leave more then 2mm from solder joint to Led, and soldering beyond the base of the tie bar is recommended.
2. Avoiding applying any stress to the lead frame while the LED are at high temperature particularly when soldering.
3. Dip and hand soldering should not be done more than one time.
4. After soldering the LED, the epoxy bulb should be protected from mechanical shock or vibration until the LED return to room temperature.
5. A rapid-rate process is not recommended for cooling the LED down from the peak temperature.
6. Although the recommended soldering conditions are specified in the above table, dip or hand soldering at the lowest possible temperature is desirable for the LED.
7. Wave soldering parameter must be set and maintain according to recommended temperature and dwell time in the solder wave.

- **Recommended soldering conditions**

Hand Soldering		Wave Soldering	
Temp. at tip of iron	300℃ Max. (30W Max.)	Preheat temp.	160℃ Max. (120 sec Max.)
Soldering time	3 sec Max.	Bath temp. & time	260 Max., 5 sec Max
Distance	2mm Min.(From solder joint to Led)	Distance	2mm Min. (From solder joint to Led)



Reliability test items and conditions：

The reliability of products shall be satisfied with items listed below.
Confidence level：97%.
LTPD:3%.

No	Item	Test Conditions	Test Hours/Cycle	Sample Size	Failure Judgment Criteria	Ac/Er
1	Solder Heat	TEMP:260℃±5℃	10 SEC	76 PCS	Iv≦Ivt*0.5 or Vf≧U or Vf≦L	0/1
2	Temperature Cycle	H:+100℃ 15min ∫ 5min L:-40℃ 15min	300 CYCLES	76 PCS		0/1
3	Thermal Shock	H:+100℃ 5min ∫ 10sec L:-10℃ 5min	300 CYCLES	76 PCS		0/1
4	High Temperature Storage	TEMP:100℃	1000 HRS	76 PCS		0/1
5	Low Temperature Storage	TEMP:-40℃	1000 HRS	76 PCS		0/1
6	DC Operating Life	TEMP:25℃ IF=20mA	1000 HRS	76 PCS		0/1
7	High Temperature / High Humidity	85℃/85%RH	1000 HRS	76 PCS		0/1


Note：Ivt：To test Iv value of the chip before the reliability test.

Iv：The test value of the chip that has completed the reliability test.

U：Upper Specification Limit.

L：Lower Specification Limit.


Packing Specification:



250PCS/Bag

1000PCS/In-Carton

10000PCS/Out-Carton



Revision History

Revision	Page	Version No.	Revision Date
Initial Release		1.0	08-23-2021
Modify the figure size	4	1.1	09-14-2022

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HARVATEK:

B1211URO-20C000134U1930 B2151IR-20C000133U1930 B2G32UDUG20C000113U1930
F10Q1USD-20C000242U1930 T15B1UYG-20C000212U1930 V1081NB--20C000342U1930
B1911UD--20D001014U1930 B2601UD--20D000123U1930 F1081IR--A1C000242U1930
B2972USUG20D000914U1930 B2102UDUG20C000133U1930 B3C73RBG02D0006H4U1930
B3SK3RGB-F6C0001HOU1930 B1861TX--05P000334U1930 B19Y1NB--20C000113U1930
HV-I8UG60G-MP9AA-U1930 B1811USD-20C000613U1930 B2102USNG20C000133U1930
B3803FCH-20C001112U1930 T15B1DND-20P000112U1930 T4642PTIRM3B000351U1930
B1591NB--20C000212U1930 B1811TX--05PP05413U1930 B2G32USNB20C000513U1930
B4301IR--20C000482U1930 T1691NB--20C000212U1930 B1591USD-20C001922U1930
B2102USNB20C000833U1930 B2591IR--20C000132U1930 B2612UYUG20D000212U1930