Blanking plug
B-1/2-20

Part number: 534216



General operating condition

Data sheet

Feature	Value
Pack size	20
Conforms to standard	DIN 908
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Nominal tightening torque	14 Nm
Tolerance for nominal tightening torque	± 20%
Product weight	43 g
Type of mounting	Internal hexagon, AF 10
Pneumatic connection 1	External thread G1/2
Note on materials	RoHS-compliant
Blanking plug material	Steel, galvanized
O-ring material	PA TPE-U(PUR)

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

NPQP-L-Q10-E-FD-P10 QSLL-G1/2-12 VABM-B10-25S-G38-6-P3 153307 DSBC-80-20-D3-PPSA-N3 HGL-1/8-QS-6 153269 CRVZS-0.4 QS-10H-6 QSML-6 SGS-M10X1,25 QSF-3/8-8-B 153031 NPQH-T-Q14-E-P10 NPQP-LQ-R18-Q8-FD-P10 QSS-8-F VBQF-U-G14-E NPQP-Y-Q6-E-FD-P10 NPQP-Y-R12-Q12-FD QS-1/2-16 153151 153367 NPQP-T-Q8-E-FD-P10 QSY-6H-4 SASC-P4-A-M8-A NPQP-D-Q4-S8-FD-P10 NPQP-LQ-R18-Q4-FD-P10 QS-1/8-8-I QSF-1/4-8-B VABM-B10-25S-G38-10