
Swing clamp cylinder
CLR-12-10-L-P-A

Part number: 535432





General operating condition

Data sheet

Feature	Value
Complete stroke	19 mm
Piston diameter	12 mm
Piston rod thread	M3
Swivel angle	90 deg +/- 4 deg
Clamping stroke	10 mm
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Structural design	Piston Piston rod Cylinder barrel
Position sensing	For proximity sensor
Swivel direction	Left
Symbol	00991217
Operating pressure	2 bar ... 10 bar
Mode of operation	Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Ambient temperature	-10 °C ... 80 °C
Effective clamping force at 2 bar	12 N
Effective clamping force at 4 bar	23 N
Effective clamping force at 6 bar	34 N
Max. clamping finger screw tightening torque	1.2 Nm
Theoretical clamping force at 6 bar	51 N
Product weight	135 g
Type of mounting	Optionally: With through-hole With internal thread With accessories
Pneumatic connection	M5
Flange screws material	Steel Galvanized
Cover material	Wrought aluminum alloy Coated
Seals material	NBR TPE-U(PU)

Feature	Value
Housing material	Wrought aluminum alloy Smooth anodized
Piston rod material	High-alloy stainless steel
Material of cylinder barrel	Wrought aluminum alloy Smooth anodized

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

QSF-1/4-8-B VABM-B10-25S-G38-6-P3 VBQF-U-G14-E NPQP-T-Q8-E-FD-P10 NPQP-LQ-R18-Q8-FD-P10 QSML-6 153367 NPQP-Y-Q6-E-FD-P10 VABM-B10-25S-G38-10 153151 153269 NPQP-L-Q10-E-FD-P10 HGL-1/8-QS-6 NPQP-LQ-R18-Q4-FD-P10 QS-1/2-16 QS-1/8-8-I QS-10H-6 QSF-3/8-8-B 153031 CRVZS-0.4 NPQP-D-Q4-S8-FD-P10 QSY-6H-4 SASC-P4-A-M8-A 153307 DSBC-80-20-D3-PPSA-N3 QSS-8-F SGS-M10X1,25 NPQH-T-Q14-E-P10 NPQP-Y-R12-Q12-FD QSLL-G1/2-12