







SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:-40°c to +105°c

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V-0)
Standard: PBT
Max.Processing Temp: 180°C for 30-60 seconds
(200°C for 10 seconds)





Ordering Information

HC-JN 254 - * - N - * - * * - **

No.of Rows 1=Single Row 2=Dual Row	No.of Pins 06-64Pin	Type Z=直针 W=弯针 S=立贴 WS=侧贴	Length (Plastic) (塑高)	Material 默认=PBT C=PA6T E=PA9T F=LCP	Contact Plating G0:Gold Flash G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin		

			GENERL TOLERANCE	制 图 DRAWING		深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM TOL	审 核 CHECK					
			X.X ±0.30	批 准 APPROVAL		产品名称 TITLE	简牛2.54 双排 弯针	版 本 REV.	A
1	初版发行		X.XX ±0.20	比 例 SCALE		产品料号 PART NO.	HC-JN254-2-N-W-8.8-XX	单 位 UNITS	mm
序号 No.	变更内容 MODIFY CONTENT	日 期 MODIFY DATE	X.XXX ±0.10 Angle ±3.°	投 影 Projection		材 料 MATERIAL		页 次 SHEET	1/1

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HCTL:

HC-PH-6AW-M HC-RJ45-5JA-2-2 PZ254-2-03-W-8.5 HC-5264-3A HC-PHD-2*2AW HC621601A-M890-A PM254-2-02-Z-8.5 PZ200-1-06-W HC-5264-3AW HC-CZ254-3-16-Z-11.5-G0-F PZ200-2-06-S PZ200-2-17-Z-C HC-AA0B010-093 HC-PA-4A PM254-1-12-W-8.5 XH-12A HC-PH-2AWT HC-SPH-2*10A PH-6A TC-0513D-4.5-260G PZ254-2-19-Z-8.5 HC-MX3.0-4AW HC-ST-003-03-Z PH-4A PZ200-1-09-Z PZ200-2-06-W PZ254-2-16-Z-8.5 HC-PA-3AWD HC-PH-T PH-2AW