


MAPX	MODIFICATION	DATE







RECOMMANDED PCB LAYOUT PCB图仅供参考

Note:
1.Material:
- 1.1 Housing: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: copper alloy,t=0.20mm
- 1.3 Shell: copper alloy,t=0.25mm

2.Specification:
- 2.1 Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.
- 2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 100 MΩ Min.
- 2.5 Total mating force: 3.57 Kgf Max.
- 2.6 Total unmating force: 1.0 Kgf Min.
- 2.7 Temperature range: -30°C~80°C

产品图
PRODUCT CHART DWG

公差一览表
TOLERANCE UNLESS OTHERMSE

X.	±0.35	X.	±5.°
.X	±0.30	.X	±2.°
.XX	±0.20	.XX	±1.°
.XXX	±0.10	.XXX	±0.5°

深圳市精拓金电子有限公司

单位 UNITS	MM	制图 DRAWING	Gavin	制图料号 PRODUCT PART NO.	920-C62A2021S10101
比例 SCALE	1:1	审核 CHKD	郭治富	产品名称 PRODUCT NO.	MICRO 5S B型5.9两脚长0.8插板无边有柱加焊脚SMT短端
日期 DATE	2016-09-09	核准 APPD	黄国荣	角法 VIEW	版本 VER A0

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Jing extension:

905-761A2032S10200 918-318K2023C40005 918-418K2022Y40011 920-C52A2021S10105
904-331B2032S10200 912-112A2021S10100 912-312A1012D10100 917-B88C201AH70201
904-232B2032S10100 920-A62A2021S10108 920-A64A2091S101A3 920-F52A2021S10105
906-262A1021D10200 911-221A2021S10100 916-151A1022Y10200 918-415K3028S40000
918-468K2029Y50000 906-752B1114D10200 907-111A1022D10200 917-P81A202ES60201
904-232A2031S10100 919-162A1012D10400 920-A62A2021S10104 906-552A1012D10200
907-312A1101Y10210 912-112A1011D10100 908-351A1011D10100 910-151A2021D10100
920-154A2021Y10110 920-C62A2021S10103