



ROHS










Recommended PCB Layout



SPECIFICATIONS

1.RATING: DC30V 1.0A
2.MECHANICAL LIFE: 10,000 CYCLES.

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
③	Shell	——	1	Phosphor Bronze	Ni Plated	——
②	Contact	——	5	Phosphor Bronze	Au Plated	——
①	Housing	——	1	LCP	Black	——

APPROVALS		DATE	HRO韩硕® ELECTRONICS CO.,LTD
DRAWN	JKUN.LU	2014/9/29	
CHECKED			TITLE: USB CONNECTOR
APPROVALS			PART NO. U-D-M5DD-W-1
TOLERANCES ARE: 30~以上 ±0.30; 10~30 ±0.25; 5~10 ±0.20; ~5 ±0.15; ANGLE ±2°			UNIT: mm; SCALE: 1:1; PROJ: ; DRAWING NO. ——; SHEET 1 OF 1

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
——	A	——	NEW	——	——	——

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HRO:

K5-1617SA-01 DA-10RP DC-031A-10A U-F-M5DD-Y-L K2-1818DP-A3SW-01 DS-01BP ES-07KP K2-1102BG-I4CW-01 U-M-M5DD-W-2 TYPE-C-31-M-04 SS-22D03-G4 U-C-M5SS-Y-1 K3-1346S-F1 K2-1102AT-A4CW-01 K2-1102DP-G4SW-04 K8-5851D-L1 K2-1102SP-A5SC-04 PJ-399B-6A U-F-M5DD-W-L K2-1101DF-A4DW-01 K2-1102DP-S3SW-04 SIM-08A U-F-M5SS-W-5 U-C-M5DW-W-1 U-F-M5DD-Y-L1 PJ-3250-5A U-F-M5DS-Y-1 K2-1102SP-K4SC-04 DQ-03BP K3-2258S-E1