



Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.








APPLICATION DIAGRAM



CODE No.	CONTACT	A	B	C	D	E	F
CL536-0401-2-21	2	1.25	4.15	7.15	5.65	1.95	2.2
CL536-0402-5-21	3	2.5	5.4	8.4	6.9	3.2	3.45
CL536-0403-8-21	4	3.75	6.65	9.65	8.15	4.45	3.1
CL536-0404-0-21	5	5.0	7.9	10.9	9.4	5.7	4.35
CL536-0405-3-21	6	6.25	9.15	12.15	10.65	6.95	5.6
CL536-0406-6-21	7	7.5	10.4	13.4	11.9	8.2	6.85
CL536-0407-9-21	8	8.75	11.65	14.65	13.15	9.45	8.1
CL536-0408-1-21	9	10.0	12.9	15.9	14.4	10.7	9.35
CL536-0409-4-21	10	11.25	14.15	17.15	15.65	11.95	10.6
CL536-0410-3-21	11	12.5	15.4	18.4	16.9	13.2	11.85
CL536-0411-6-21	12	13.75	16.65	19.65	18.15	14.45	13.1
CL536-0413-1-21	14	16.25	19.15	22.15	20.65	16.95	15.6
CL536-0414-4-21	15	17.5	20.4	23.4	21.9	18.2	16.85

RECOMMENDED PATTERN



NOTES
1. WHEN THIS CONNECTOR MATES WITH DF13-*S-1.25C, THE MATING LENGTH IS 5.8mm.
2. WHEN THIS CONNECTOR HAS TWO OR THREE CONTACTS, THE LOCK SHALL BE SET AT THE CENTER OF HOUSING. IF MORE THAN FOUR, THE TWO LOCKS SHALL BE SET AS SHOWN ON THIS DRAWING.
3. LEAD CO-PLANARITY INCLUDING REINFORCED METAL FITTINGS SHALL BE WITHIN 0.1mm.
4. AREA TO PICK AND PLACE.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	PHOSPHOR BRONZE	SURFACE: TIN PLATED 1μm min.			
2	BRASS	SURFACE: TIN PLATED 1μm min.	5	POLYESTER	COVER TAPE, CLEAR
1	POLYAMIDE	UL94V-0, (BEIGE)	4	PS	EMBOSSED CARRIER TAPE, CLEAR

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	1	8	DIS-H-005399	TS. KUMAZAWA	HK. UMEHARA	10.12.14


HIROSE ELECTRIC CO., LTD.


APPROVED	TY. OMA	05.10.31
CHECKED	HK. UMEHARA	05.10.31
DESIGNED	TS. KUMAZAWA	05.10.31
DRAWN	AK. MIURA	05.10.27


DRAWING NO.	EDC3-083672-03
PART NO.	DF13C-*P-1.25V(21)
CODE NO.	CL536- 1 1/2

HRS DRAWING FOR REFERENCE

Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.








CODE No.	CONTACT	G	H	J	K	L
CL536-0401-2-21	2	13.5	16		7.5	16.4
CL536-0402-5-21	3	13.5	16		7.5	16.4
CL536-0403-8-21	4	21.5	24		11.5	24.4
CL536-0404-0-21	5	21.5	24		11.5	24.4
CL536-0405-3-21	6	21.5	24		11.5	24.4
CL536-0406-6-21	7	21.5	24		11.5	24.4
CL536-0407-9-21	8	21.5	24		11.5	24.4
CL536-0408-1-21	9	21.5	24		11.5	24.4
CL536-0409-4-21	10	21.5	24		11.5	24.4
CL536-0410-3-21	11	26	32	28.4	14.2	32.4
CL536-0411-6-21	12	26	32	28.4	14.2	32.4
CL536-0413-1-21	14	26	32	28.4	14.2	32.4
CL536-0414-4-21	15	37	44	40.4	20.2	44.4

9 DETAIL OF PART No. LABEL


DATE OF MANUFACTURED	年 月 日
CODE No.	
PART No.	DF13C-*P-1.25V(21)
QUARITY	1000ko
SUPPLIER	HIROSE ELECTRIC CO.,LTD.

HRS DRAWING FOR REFERENCE

N(10:1)



STYLE AND DIMENSION OF REEL



NOTES 5 1REEL : 1000 CONNECTORS.
6 AT THE BEGINNING OF THE REEL, 30 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL, 20 COMPONENTS SHALL BE EMPTY.
7 WHEN THE TAPE WIDTH IS 32 OR 44mm, SPROCHET HOLES SHALL BE SET ON BOTH SIDES OF REEL AS SHOWN ON THIS DRAWING.
8 WHEN THE TAPE WIDTH IS 44mm OR OVER, THE TOLERANCE SHALL BE 2±0.15.
9 DETAIL OF PART No. LABEL IS WRITTEN IN JAPANESE.
10 PEEL FORCE BETWEEN EMBOSSED CARRIER TAPE AND COVER TAPE IS 0.1~0.7N.

HRS	DRAWING NO.	EDC3-083672-03
	PART NO.	DF13C-*P-1.25V(21)
	CODE NO.	CL536- 1 2/2

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Hirose Electric:

BM29B0.6-4DS/2-0.35V(51) FH72-21S-0.3SHW FX18-60S-0.8SH FX8-120S-SV(22) DF22A-1416SCFA DF65-4P-1.7V(21) FH35C-19S-0.3SHW(50) RM15TP-2PA(81) ZE05-24DP-2H ZE05H-12DP-2H ZE064W-8DP-HU/R(A) DF57AH-5S-1.2C DF59M-2224PCF GT8E-6S-HU RM12BRD-2PH(81) DF19A-3032SCFA(41) DF36A-25P-SHL ZE05H-4P-2V(A) DF52-4P-0.8C FH41-50S-0.5SH(28) FX18-80S-0.8SH ZH05-20DP-HU(B) DF11-16DP-2DSA(24) DF17(3.0)-40DS-0.5V(57) DF33C-4S-3.3C RM15TRH-10PH(81) DF62C-4S-2.2C DF40C-50DP-0.4V(51) FH41-30S-0.5SH(05) HDE-CTH(10)