OptiMOS™-T2 Power-Transistor

AEC Qualified

RoHS


Product Summary


V_{DS}	30	V
$R_{DS(on)}$	1.05	mΩ
I_D	180	A

Features

- N-channel - Enhancement mode
- AEC qualified
- MSL1 up to 260°C peak reflow
- 175°C operating temperature
- Green package (RoHS compliant)
- Ultra low Rds(on)
- 100% Avalanche tested

PG-TO263-7-3





Type	Package	Marking
IPB180N03S4L-01	PG-TO263-7-3	4N03L01

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	T_C=25°C, V_{GS}=10V[1)]	180	A
		T_C=100 °C, V_{GS}=10 V[2)]	180	
Pulsed drain current[2)]	$I_{D,pulse}$	T_C=25 °C	720	
Avalanche energy, single pulse[2)]	E_{AS}	I_D=90 A	530	mJ
Avalanche current, single pulse	I_{AS}	-	180	A
Gate source voltage	V_{GS}	-	±16	V
Power dissipation	P_{tot}	T_C=25 °C	188	W
Operating and storage temperature	T_j, T_{stg}	-	-55 ... +175	°C
IEC climatic category; DIN IEC 68-1	-	-	55/175/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics[2]						
Thermal resistance, junction - case	R_{thJC}	-	-	-	0.8	K/W
SMD version, device on PCB	R_{thJA}	minimal footprint	-	-	62	
		6 cm^2 cooling area[3]	-	-	40	
Electrical characteristics, at T_j=25 °C, unless otherwise specified						
Static characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0 V, I_D= 1 mA	30	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=140 µA	1	1.5	2.2	
Zero gate voltage drain current	I_{DSS}	V_{DS}=30 V, V_{GS}=0 V, T_j=25 °C	-	0.01	1	µA
		V_{DS}=18 V, V_{GS}=0 V, T_j=85 °C[2]	-	5	60	
Gate-source leakage current	I_{GSS}	V_{GS}=16 V, V_{DS}=0 V	-	1	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=4.5 V, I_D=90 A	-	1.2	1.4	mΩ
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=10 V, I_D=100 A	-	0.9	1.05	mΩ

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics[2]						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=25 V, f=1 MHz	-	13500	17600	pF
Output capacitance	C_{oss}		-	3370	4400	
Reverse transfer capacitance	C_{rss}		-	125	250	
Turn-on delay time	$t_{d(on)}$	V_{DD}=15 V, V_{GS}=10 V, I_D=100 A, R_G=1.6 Ω	-	8	-	ns
Rise time	t_r		-	5	-	
Turn-off delay time	$t_{d(off)}$		-	57	-	
Fall time	t_f		-	23	-	
Gate Charge Characteristics[2]						
Gate to source charge	Q_{gs}	V_{DD}=24 V, I_D=180 A, V_{GS}=0 to 10 V	-	39	51	nC
Gate to drain charge	Q_{gd}		-	25	50	
Gate charge total	Q_g		-	187	239	
Gate plateau voltage	$V_{plateau}$		-	3.1	-	V
Reverse Diode						
Diode continous forward current[2]	I_S	T_C=25 °C	-	-	180	A
Diode pulse current[2]	$I_{S,pulse}$		-	-	720	
Diode forward voltage	V_{SD}	V_{GS}=0 V, I_F=100 A, T_j=25 °C	-	0.9	1.3	V
Reverse recovery time[2]	t_{rr}	V_R=20 V, I_F=100A, di_F/dt=100 A/µs	-	180	-	ns
Reverse recovery charge[2]	Q_{rr}		-	200	-	nC


[1] Current is limited by bondwire; with an R_{thJC} = 0.8 K/W the chip is able to carry 335A at 25°C.

[2] Defined by design. Not subject to production test.

[3] Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm^2 (one layer, 70 µm thick) copper area for drain connection. PCB is vertical in still air.


1 Power dissipation

$P_{tot} = f(T_C)$; $V_{GS} \geq 6$ V



2 Drain current


$I_D = f(T_C)$; $V_{GS} \geq 6$ V



3 Safe operating area

$I_D = f(V_{DS})$; $T_C = 25$ °C; $D = 0$


parameter: t_p



4 Max. transient thermal impedance

$Z_{thJC} = f(t_p)$


parameter: $D = t_p / T$



5 Typ. output characteristics

$I_D = f(V_{DS})$; $T_j = 25$ °C


parameter: V_{GS}



6 Typ. drain-source on-state resistance

$R_{DS(on)} = (I_D)$; $T_j = 25$ °C


parameter: V_{GS}



7 Typ. transfer characteristics


$I_D = f(V_{GS})$; $V_{DS} = 6$V

parameter: T_j



8 Typ. drain-source on-state resistance


$R_{DS(on)} = f(T_j)$; $I_D = 80$ A; $V_{GS} = 10$ V



9 Typ. gate threshold voltage


$V_{GS(th)} = f(T_j)$; $V_{GS} = V_{DS}$

parameter: I_D



10 Typ. capacitances


$C = f(V_{DS})$; $V_{GS} = 0$ V; $f = 1$ MHz



11 Typical forward diode characteristicis

IF = f(V_{SD})


parameter: T_j



12 Typ. avalanche characteristics

$I_{AS} = f(t_{AV})$


parameter: $T_{j(start)}$



13 Typical avalanche energy


$E_{AS} = f(T_j)$

parameter: I_D



14 Drain-source breakdown voltage


$V_{BR(DSS)} = f(T_j)$; $I_D = 1$ mA




15 Typ. gate charge

$V_{GS} = f(Q_{gate})$; $I_D = 80$ A pulsed

parameter: V_{DD}



16 Gate charge waveforms



Published by
Infineon Technologies AG
81726 Munich, Germany

© Infineon Technologies AG 2008
All Rights Reserved.

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings
Due to technical requirements, components may contain dangerous substances.
For information on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life.
If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Revision History

Version	Date	Changes

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Infineon Technologies:

TLE5046IC-AK-LR TLE6250G V33 IPW60R070CFD7 BSC077N12NS3 G IPF012N06NF2SATMA1 TD340N22KOFXPSA1 TLS4120D0EPVXUMA1 IMWH170R450M1XKSA1 IPD60R280P7S CY8C29466-24SXIT IPB042N10N3 G IRFP2907PBF CY15V108QN-20LPXC EVALPMG1B1DRPTOBO1 IDH12SG60C IPD60R360P7S IPF010N04NF2SATMA1 IR2302STRPBF IR3895MTRPBF IRF3710PBF BSS126IXTSA1 BTS 5210 G IPW60R018CFD7XKSA1 IRF5210PBF IRF7820TRPBF IRFS4227TRLPBF FF800R12KE7EHPSA1 IPT60R016CM8XTMA1 IRF7853TRPBF TDA21590