
Photologic® Reflective Object Sensor

OPB715Z, OPB716Z, OPB717Z, OPB718Z



Features:

- Focused for maximum sensitivity
- .5” (12.700 mm) sensing distance
- Panel mount
- Choice of output configurations
- 18” (457.200 mm) minimum wire length

Description:

The **OPB715Z** series reflective assembly consists of a GaALAs LED and a Photologic® sensor enclosed in an IR transmissive housing. The sensor is characterized to detect paper at 0.5” (12.7 mm). The sensor has a wide operating distance range and is capable of detecting reflective objects at other distances. The reflective distance depends on the reflectance materials.


These devices are designed to replace conventional mechanical limit switches where long life and reliability are critical. The switches are designed to easily snap mount into a 0.036 inch (0.914 mm) 20 gage thick material with a rectangular opening of 0.315” x 0.472 “ (8.0 mm x 12.0 mm).

The sensor’s panel-mount plastic housing shields stray light and is terminated with 18” (457 mm) UL approved 26 AWG wire leads. The LED is current limited internally for design convenience. Its output can be specified as either TTL Totem-Pole or TLL Open-Collector. Inverted output options are available for either output configuration.

Applications:


- Focused for maximum sensitivity
- 0.5” (12.700 mm) sensing distance
- Panel mount
- Choice of output configurations
- 18” (457.200 mm) minimum wire length

Part Number	LED Peak Wavelength	Sensor Photologic®	Reflection Distance Inch (mm)	Lead Length / Spacing
OPB715Z	890 nm	Totem-Pole	0.50"	18" / 26 AWG Wire
OPB716Z		Open-Collector		
OPB717Z		Inv-Totem-Pole		
OPB718Z		Inv-Open-Collector		




DIMENSIONS ARE IN: **[MILLIMETERS]** **INCHES**


OPB715 Buffered Totem-Pole




OPB716 Buffered Open Collector



OPB717 Inverted Totem-Pole



OPB718 Inverted Open-Collector



Color-Pin #	Description
Orange	V_{CC}
White	Output
Violet	Ground

RoHS

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics’ own data and is considered accurate at time of going to print.

© TT electronics plc

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Electrical Specifications

Absolute Maximum Ratings (T_A = 25° C unless otherwise noted)	
Storage & Operating Temperature Range	-40° C to +85° C
Supply Voltage, V_{CC} (not to exceed 2 seconds)	10 V
Power Dissipation(1)	300 mW
Output Voltage (Open-Collector only)	35 V

Electrical Characteristics (T_A = 25° C unless otherwise noted, see OPL560 series for additional electrical information)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
V_{CC}	Operating Supply Voltage	4.75	-	5.25	V	-
I_{CCL}	Low-Level Supply Current:	-	-	30	mA	V_{CC} = 5.0 V, output open
I_{CCH}	High-Level Supply Current	-	-	50	mA	V_{CC} = 5.0 V, output open
I_{OH}	High Level Output Current OPB716 OPB718	- -	- -	100 100	µA µA	V_{OH} = 30 V, E_E = 1 mW/cm^2 V_{OH} = 30 V, E_E = 0
I_{OS}	Short Circuit Output Current OPB715 OPB717	- -	- -	100 100	µA µA	V_{CC} = 5.0 V, V_{CH} = 5 V
V_{OH}	High Level Output Voltage OPB715, OPB717 OPB716, OPB718	V_{CC} - 2.1 V_{CC} - 2.1	- -	- -	V V	I_{OH} = -1 µA, E_E = 1 mW/cm^2 I_{OH} = -1 µA, E_E = 0
V_{OL}	Low Level Output Voltage OPB715, OPB717 OPB716, OPB718	- -	- -	.4 .4	V V	I_{OL} = 16 mA, E_E = 0 I_{OL} = 16 mA, E_E = 1 mW/cm^2

Notes:


(1) Derate linearly at 5.0 mW / °C above 25° C.
(2) Terminating wire is 7 strand, 26 AWG, UL 1429.
(3) Tested at d = 0.55" (12.7 mm) from a 90% diffuse, white test surface. Reference: Eastman Kodak Catalog #E 152 7795.
(4) No reflective surface.

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


© TT electronics plc

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com


Typical - Voltage vs Displacement
Kodak 90%




Typical - Voltage vs Displacement
Kodak 19% & Retroreflective



Typical - Voltage vs Displacement
Copy Paper



Typical - Voltage vs Displacement
Avery Label 5160




General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


© TT electronics plc

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Typical - Trigger Points vs Displacement From Both Sides



Typical - Trigger Points vs Displacement From Top & Bottom



General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT electronics plc

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TT Electronics:

WHS3-33RJA1 BPR10101J OARS-XP-0R001 W24-33KJI WH10-100RJI WH25-8R2JI APC0805RD-10KBT5 ASC1206-150KFT5 OPB802W55Z WA84-180RJI CAW104R70JLF OAR5 - R020FI P160KNP-0QC20A10K PCF0402PR-180RBT1 PCF0603PR-1K-BT1 PCF0603R-100KBT1 RC55Y-210KBI WCR0805-82KFI SQP7S-82RJB15 WP4S-1R5JA2 LR1206-R10FW LRMAP3920C-R001FT OPB829CZ OVLBB4C7 WH5-50RJI 67WR5KLFTB MFC0805-R10FT5 MFR3-10RFC WCR1206-200KFI WDBR122RKT