- Material = Crosslinked Silicone Elastomer
- Color = Black

Electrical Characteristics:
- Product Source = U.K., U.S.
- Expanded ID, Min. (mm [in]) = 50.80 [2.000]
- Recovered ID, Max. (mm [in]) = 29.00 [1.142]
- Product Use = Cables, Electronic Components, Harnesses, Wire Splices

Body Features:
- Product Name = SFR
- Pliancy = Very Flexible
- Wall Style = Medium
- Wall Type = Single
- Shrink Ratio = 1.75:1
- Fluid Type = Aviation Fuel, Brake Fluid, Hydraulic Fluid, Lubricating Oil, Water
- Resistant To = Fluids, Strain
- Wall Thickness - Full Recovery (Nominal) (mm [in]) = 2.79 [0.110]

Housing Features:
- Material Systems = No
- Flammability Rating Type = Flame-Retardant

Industry Standards:
- Government/Industry Qualification = Yes
- Government/Industry Part Number = M23053/10-012-0
- UL Rating = None
- CSA Certified = No
- Approved Standards = MIL-PRF-46846 Type II Class 1, SAE AMS-DTL-23053/10
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for U
- Full Recove
- Shrink Temp
- High Tempe

Operation/Appli
- Application
- Emission Fr

Packaging Featu
- Packaging M

Other:
- Brand = Ra

© 2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company. All Rights Reserved | Privacy Policy

Downloaded from Arrow.com.