■ Features

- High density packaging with a pitch of 2.54mm(0.1 inch) max. is possible. This series requires less space and has greater EMI suppression effects.
- Different types with the same shape are available**.**
- Excellent in physical properties,such as terminal strength,flexure strength, soldering resistance and soderability.
- Applicable to both flow and reflow soldering.
- High impedance cover wide frequency ranges.
- YI series can be used in high current circuits due to its low DC resistance.
- Operating temperature:-40℃ ~ +125℃.

■ Applications

- Computers and peripheral devices,personal computers,VCR and cameras.
- Noise suppression in digital equipments,car stereo,car engines controllers and OA electronic instruments.
- Communication equipment.

■ Product Identification

YI □□□□□□ □ □□□ - □□□□
(1) (2) (3) (4) (5)

(1)： Type


(2)： Dimensions

(3)： Material Code

(4)： Impedance

(5)： Rated Current

Shapes and Dimensions (Unit：mm)



TYPE	A	B	C	D	L	W	G
YI201209	2.0±0.2	1.2±0.2	0.9±0.2	0.5±0.3	3.20	1.50	0.60

Electrical Requirements


Part Number	Impedance(Ω) ±25%	Test Freq. (MHz)	DCR MAX. (Ω)	Rating Current MAX (A)
YI201209U101-6R0T	100	100	0.02	6.0

TEST INSTRUMENTS：



HP 4338A MILLIOHMMETER

HP 4291B RF IMPEDANCE/MATERIAL ANALYZER

Impedance VS. Frequency characteristic




Reliability test

Item	Performance	Test condition
Operating temperature range	-55 °C to + 125 °C	
Storage temperature and umidity ranges	40 °C MAX., 70% RH MAX.	
Soldering heat resistance	The chip shall not be cracks. More than 75% of terminal electrode shall be covered with solder.	Preheat: 150 °C, 60 seconds Solder temperature : 270 ± 5 °C Flux: Rosin Dip time: 10 ± 1 seconds 
Solderability	More than 90% of the terminal electrode shall be covered with new solder.	Preheat: 150 °C, 60 seconds Solder temperature: 245 ± 5 °C Flux: Rosin Dip time: 4 ± 1 seconds 





Recommended Soldering Conditions

(REFLOW TEMPERATURE PROFILE) Lead-Free


A	260 ± 5℃
B	230 ± 5℃
C	30 ±10 sec
D	150℃
E	180℃
F	90 ± 30sec




Reliability test

Item	Performance	Test condition
High temperature resistance	Appearance: Ferrite shall not be damaged. Impedance: Within±20% of the initial value.	Temperature: 85±2℃ Testing time: 1008±12 hours Measurement: After placing for 24 hours min. 
Humidity resistance	Appearance: Ferrite shall not be damaged. Impedance: Within±20% of the initial value	Humidity: 90 to 95% RH Temperature: 40±2℃ Testing time: 1008±12 hours Measurement: After placing for 24 hours min. 
Thermal Shock	Appearance: Cracking, chipping or any other defects harmful to the characteristics shall not be allowed. Impedance: Within±20% of the initial value	Temperature: -40℃, +85℃, kept stabilized for 30 minutes each Cycle: 100 cycles Measurement: After placing for 24 hours min. 
Low temperature storage life test	Appearance: Cracking, chipping or any other defects harmful to the characteristics shall not be allowed. Impedance: Within±20% of the initial value.	Temperature: -40±2℃ Testing time: 1008±12 hours Measurement: After placing for 24 hours min. 


■ Taping Dimensions(Unit:mm)






Material:Paper						
TYPE	A	B	W	P	T	CHIPS/REEL
100505	0.62	1.12	8	2	0.60	10000
160808	1.10	1.90	8	4	0.95	4000
201209	1.50	2.30	8	4	0.95	4000
Material:Polystyrene						
TYPE	A	B	W	P	T	CHIPS/REEL
160808	1.01	1.80	8	4	1.02	4000
201209	1.42	2.25	8	4	1.04	4000
201212	1.50	2.35	8	4	1.45	3000
321611	1.88	3.50	8	4	1.27	3000
322513	2.77	3.42	8	4	1.55	2000
451616	1.93	4.95	12	4	1.93	2000
453215	3.66	4.95	12	8	1.85	1000
YA3216M4	1.88	3.50	8	4	1.40	3000

■ Reel Dimensions(Unit:mm)



TYPE	8mm	12mm
A	178±2	178±2
B	21.0±0.8	21.0±0.8
C	13.0±0.8	13.0±0.8
G	10.0	14.0
N	75	75
T	12.5	16.5

■ Direction of rolling



Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

YJYCOIN:

YP0705-680M YNR1050-271M YI100505U121-1R2T YI321611U601-3R0T YLCM0904-471T YNR6045-330M YSPI1050-101M YSPIA1770-100M YDFW1515T-302L03015 YPRH3D16-330M YSMC2016S-R24M YI201209U800-6R0T YPRH1207-150M YPRH1207-4R7M YPRH1209-470M YSPI0630A-1R0M YSPI0730-R22M YNR2016-3R3M YNR4030-6R8M YP0402-330M YSFP2915S-6R8M CD32YP0302-4R7M CD54YP0504-101M CD75YP0705-102M YLM1211-222T YSPIA1770-101M YWLD2012-3R3K YLM1211-202T YLM2012-900T YAL0204-151K