Clevis foot
CRLBN-12/16

Part number: 161862



General operating condition

Data sheet

Feature	Value
Size	12/16
Mounting position	Any
Corrosion resistance class (CRC)	4 - Particularly high corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Suitability for the production of Li-ion batteries	Metals with more than 1% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils
Ambient temperature	-40 °C ... 150 °C
Product weight	39 g
Note on materials	RoHS-compliant
Mounting material	High-alloy stainless steel
Bolt material	High-alloy stainless steel
Fuse material	High-alloy stainless steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

QS-1/2-16 QSF-3/8-8-B NPQP-LQ-R18-Q8-FD-P10 NPQP-T-Q8-E-FD-P10 QS-1/8-8-I QSS-8-F 153269 QSML-6 VABM-B10-25S-G38-10 NPQP-L-Q10-E-FD-P10 NPQP-Y-Q6-E-FD-P10 153367 QSF-1/4-8-B SGS-M10X1,25 QSY-6H-4 SASC-P4-A-M8-A CRVZS-0.4 DSBC-80-20-D3-PPSA-N3 HGL-1/8-QS-6 NPQP-D-Q4-S8-FD-P10 VABM-B10-25S-G38-6-P3 153151 153307 NPQH-T-Q14-E-P10 QS-10H-6 VBQF-U-G14-E 153031 QSLL-G1/2-12 NPQP-LQ-R18-Q4-FD-P10 NPQP-Y-R12-Q12-FD