



目錄 MAPX	设变内容 MODIFICATION	日期 DATE

备注：侧弹分为外弹与内弹










RBC□MMENDBD P.C.B PATTBRN LAY□ UT



NOTES:
Housing: Thermoplastics,UL94V-0
Contact: Copper Alloy
Shell: Copper Alloy/Steel
Voltage Current Rating: 1.5 AMP. 30V AC
Insulation Resistance: 1000MΩ Min.
Contact Resistance: 30 MΩ Max.
Dielectric Withstanding Voltage: 500W AC
Temperature Range: -35℃ to +85℃
Insulator color: Black/White
Plastic material: PBT/LCP/Others
Shell finish: Nickel plated/Tin-Lead plated
Mechanical:
Mating Force: 3.5KG MAX
Unmating Force: 0.7 KG MIN.(END 1500 TIMES)
Contact finish:
01: Selective Gold Flash
02: Selective Gold 3U"
03: Selective Gold 5U"
04: Selective Gold 15U"
05: Selective Gold 30U"

产品图 PRODUCT CHART DWG			
公差一览表 TOLERANCE UNLESS OTHERWISE			
X.	±0.25	X°.	±5°
.X	±0.20	.X°	±2°
.XX	±0.15	.XX°	±1°
.XXX	±0.10	.XXX°	±0.5°

深圳市精拓金电子有限公司

单位 UNITS	MM	制图 DRAWING	Z-Y-B	产品料号 PRODUCT PART NO.	901-131A1013D10101
比例 SCALE	1:1	审核 CHKD	雷永键	产品名称 PRODUCT NO.	AF90度外扣直脚有边内弹16.3铁壳一型加宽PBT白胶 改胶芯
日期 DATE	2013.08.10	核准 APPD	雷永键	角法 VIEW	版本 VER A0

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Jing extension:

905-761A2032S10200 906-752B1114D10200 908-351A1011D10100 916-151A1022Y10200
918-415K3028S40000 918-418K2022Y40011 919-162A1012D10400 920-C62A2021S10103
904-232B2032S10100 904-331B2032S10200 906-262A1021D10200 906-552A1012D10200
910-151A2021D10100 904-232A2031S10100 907-111A1022D10200 912-112A2021S10100
912-312A1012D10100 920-A64A2091S101A3 920-F52A2021S10105 917-B88C201AH70201
918-468K2029Y50000 920-154A2021Y10110 920-A62A2021S10108 907-312A1101Y10210
912-112A1011D10100 920-A62A2021S10104 911-221A2021S10100 917-P81A202ES60201
918-318K2023C40005 920-C52A2021S10105