
Compact air cylinder
ADVU-50-10-P-A

Part number: 156550





General operating condition

Data sheet

Feature	Value
Stroke	10 mm
Piston diameter	50 mm
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Mode of operation	Double-acting
Piston rod end	Internal thread
Structural design	Piston Piston rod
Position sensing	For proximity sensor
Symbol	00991217
Variants	Piston rod at one end
Operating pressure	0.08 MPa ... 1 MPa
Operating pressure	0.8 bar ... 10 bar
Operating pressure	11.6 psi ... 145 psi
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-20 °C ... 80 °C
Impact energy in the end positions	0.64 J
Theoretical force at 6 bar, retracting	1057 N
Theoretical force at 6 bar, advancing	1178 N
Moving mass at 0 mm stroke	112 g
Additional moving mass per 10 mm stroke	16 g
Basic weight with 0 mm stroke	560 g
Additional weight per 10 mm stroke	72 g
Type of mounting	Optionally: With through-hole With accessories
Pneumatic connection	G1/8
Flange screws material	Steel, galvanized
Cover material	Wrought aluminum alloy
Material of dynamic seals	NBR TPE-U(PU)
Piston rod material	High-alloy steel
Material of cylinder barrel	Wrought aluminum alloy

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

NPQH-T-G38-Q8-P10 QSL-12 DFM-63-100-P-A-KF DSBC-32-40-D3-PPVA-N3 NPQH-D-Q14-E-P10 SEA-3GS-M8-S DSBC-32-50-D3-PPVA-N3 QS-G1/8-6-I QS-G3/8-12 QSLV-G1/4-6 QSLV-G1/8-8 SPTW-P16R-G14-A-M12 VABM-B10-25S-G38-6 NPQH-D-S14-Q8-P10 DSBC-50-20-D3-PPSA-N3 HGL-1/8-B NPQP-D-R38-Q10-FD-P10 VABM-B10-25S-G38-4-P3 NPQH-D-Q12-Q8-P10 QSLV-G1/2-12-I VABM-L1-18S-G38-10 VABM-L1-10HW-G18-4-GR DSBC-40-160-D3-PPSA-N3 DSBC-40-50-D3-PPSA-N3 DSBC-63-320-D3-PPVA-N3 QSL-1/4-4 153034 NPQP-D-R14-Q10-FD-P10 VABM-B10-20S-G14-6 VABM-L1-14W-G14-4-GR