
CUI DEVICES

SERIES: RDS-74385-SMT | **DESCRIPTION:** ROTARY DIP SWITCH

FEATURES

- 10 and 16 positions
- flat actuator
- surface mount
- tube or tape and reel packaging



SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated voltage	switching non-switching			42 42	Vdc Vdc
rated current	switching non-switching			100 400	mA mA
withstanding voltage	for 1 minute		250		Vac
contact resistance				80	mΩ
insulation resistance	at 250 Vdc	100			MΩ
operating torque		90	120	150	gf*cm
actuator travel	continuous rotation		360		degrees
operating temperature		-60		125	°C
storage temperature		-60		125	°C
life	at rated voltage, current, 15~20 cycles/minute		25,000		steps
flammability rating	UL94V-0				
RoHS	yes				
IP level	IP67 (IEC 60529:2001)				

PART NUMBER KEY

RDS - XXS - 74385 - SMT - XX


- RDS: Base Number
- XX: No. of Positions: 10 =10 Positions; 16 =16 Positions
- XX: Packaging: "blank" = Tube; TR = Tape and Reel

MECHANICAL DRAWING


units: mm
tolerance: ±0.3 mm
unless otherwise noted

ITEM	DESCRIPTION	MATERIAL	PLATING/COLOR
1	actuator	LCP (UL94V-0)	red (10 position) gray (16 position)
2	housing	LCP (UL94V-0)	black
3	face plate	stainless steel	
4	terminals	copper alloy	gold


10 POSITION





16 POSITION



ON ○					
OFF ●		CODE			
TYPE	POS	1	2	4	8
10 STEP	0	●	●	●	●
	1	○	●	●	●
	2	●	○	●	●
	3	○	○	●	●
	4	●	●	○	●
	5	○	●	○	●
	6	●	○	○	●
	7	○	○	○	●
	8	●	●	●	○
	9	○	●	●	○
16 STEP	A	●	○	●	○
	B	○	○	●	○
	C	●	●	○	○
	D	○	●	○	○
	E	●	○	○	○
	F	○	○	○	○








Recommended PCB Layout
Top View

SOLDERABILITY


parameter	conditions/description	min	typ	max	units
hand soldering	for maximum 3 seconds			350	°C
reflow soldering		255		260	°C



PACKAGING (TUBE)

units: mm


Tube Size: 13.0 x 14.50 x 540 mm
Tube QTY: 70 pcs



PACKAGING (TAPE & REEL)

units: mm

Reel Size: Ø330 mm
QTY: 600 pcs



REVISION HISTORY

rev.	description	date
1.0	initial release	10/06/2020

The revision history provided is for informational purposes only and is believed to be accurate.

CUI DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

cuidevices.com

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Same Sky:

RDS3-8S-1065-1-SMT-TR PTN06-B100CB20 DEVKIT-ECM-001 PTN09S1-H500120K1B TBL006V-500-03GY-2GY PJ-202A TBP01P1-508-02BE TBL004-508-23BE-2GY RCJ-61223344 RDS6-16S-1065-SMT-TR SJ-43504-SMT-TR MSS-102545-14A-90-D CDM1232-04A-02MST-1M-67 CBL-UC-UC-10BP TBL004-508-16BE-2GY MSIM-4-A CMM-3729AB-38308-TR UJ31-CH-G2-SMT-TR CLS0301MA-L152 PTN09S1-H10120DB CEM-1201S CMS-16093-078L100 MSIM-7-A SJ-2523-SMT-TR CMS-16093-078L100A PJ1-022-SMT-TR RDS3-8S-1012-2-RA-254-D PTN09S2-H05120K1A SJ2-35954A-SMT-TR CLS0571M-L152