RAFIX 22 QR - Selector switch, illuminated, round collar, short handle

1.30.242.427/2200



Included: Ring nut with claw.

Other handle marking colors available on request.

A contact block in position 3 or 5/6 (centre) is actuated when turning in either direction.

General information	
Actuator	handle
Marking of handle	white
Color of front ring	silver metallic
Form of collar	round

Dimensions	
Dimensions of collar	ø 29.8 mm
Overall height	22.2 mm
Mounting depth with contact block without cable	56.4 mm
Mounting hole	ø 22.3 mm
Mounting grid	50 x 30 mm
Diameter of collar	29.8 mm

Mechanical design	
Mounting	ring nut
Contact function	latching 1 x 90° and momentary 1 x 40°
Illumination	yes
Rotating angle	1 x 90° and 1 x 40°

Mechanical characteristics	
Operating force max.	approx. 5 N for 1 switching element
Torque max.	2 Nm


Electrical characteristics	
Protection class	II


Other specifications	
Operating life (operations)	500,000 cycle
Degree of protection from front side	IP65 (DIN EN 60529)
Ambient temp. operating min.	-25 °C
Ambient temp. operating max.	+70 °C
Storage temperature min.	-40 °C
Storage temperature max.	+80 °C
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78


Technical data are approximate and intended solely for general orientation in the selection of a product.
Subject to modifications and errors. Images and other graphics may only be similar.
For more information, refer to www.rafi.de chapter Imprint / Data Protection.

ROHS compliant	yes
REACH compliant	yes

Panel cut-out to IEC 60947-5-1







Technical data are approximate and intended solely for general orientation in the selection of a product.
Subject to modifications and errors. Images and other graphics may only be similar.
For more information, refer to www.rafi.de chapter Imprint / Data Protection.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

RAFI:

1.11.011.001/0550	1.20.126.202/0000	1.30.253.501/0300	1.15.213.003/0000	1.30.070.001/1002
1.30.270.231/2500	3.14.002.062/0000	1.30.074.121/0301	1.74.508.001/2200	5.92.025.368/0000
1.10.107.011/0507	1.15.105.112/0000	1.15.106.503/1400	1.30.074.501/0304	1.30.270.011/0108
1.69.508.861/1301	5.05.511.475/2600	1.01.102.011/0507	1.10.011.001/0221	5.49.233.008/1002
1.20.126.104/9000	1.24.200.001/0000	1.30.243.501/0300	1.69.508.810/0000	5.46.167.042/0209
1.15.106.021/1002	5.05.511.747/1300	1.14.002.106/0000	1.30.270.001/2307	5.05.511.641/0000