NOTES:

1. MATERIALS AND FINISHES:

   SMA CRIMP PLUG - P/N: 132114
   SMA BULKHEAD CRIMP JACK - P/N: 132119
   CABLE - RG 316/U COAXIAL CABLE


2. ELECTRICAL:

   A. IMPEDANCE: 50 OHM, NOMINAL


3. PACKAGING:

   A. QUANTITY: SINGLE PACK
   B. BAG TO BE MARKED: AMPHENOL RF, 135110-01-XX.XX, AND DATE CODE

135110-01-XX.XX	REVISIONS				
DRAWING NO.	REV	DESCRIPTION	DATE	ECO	APPR
THIRD ANGLE PROJ.	NC	INITIAL RELEASE	04-Feb-09	--	--
	B	SEE SHEET 1	26-Mar-14	2714	CL/BCG



SCALE 0.625



ORDERING INFORMATION		
PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH IN INCHES * [METERS]
135110-01-06.00	-	6.00 [0.152]
-	135110-01-M0.25	9.84 [0.250]
135110-01-12.00	-	12.00 [0.305]
135110-01-18.00	-	18.00 [0.457]
-	135110-01-M0.50	19.69 [0.500]
135110-01-24.00		24.00 [0.610]
-	135110-01-M0.75	29.53 [0.750]
135110-01-36.00		36.00 [0.914]
-	135110-01-M1.00	39.37 [1.000]
135110-01-48.00	-	48.00 [1.219]

* ADDITIONAL LENGTHS CAN BE PROVIDED.
CONTACT AMPHENOL RF MARKETING FOR QUOTE

TOLERANCE TABLE	
LENGTH IN INCHES/FT [METERS]	TOLERANCE
0" - 23.90" [0 - 0.607]	±0.25" [0.006]
24.00" - 59.00" [0.610 - 1.499]	±0.50" [0.013]
5.0' - 24.9' [1.524 - 7.617]	±2.5%
25.0' & UP [7.620 & UP]	±5.0%

DESIGN REQUIREMENTS:

- [X] FREQUENCY : DC TO 3.0 GHz
- [ ] VSWR : ____1 MAX
- [ ] INS. LOSS : ---- dBMAX
- [X] CONTINUITY
- [X] HI-POT : 500 VRMS
- [ ] OTHER

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE AS FOLLOWS:
2 PLACE DECIMAL ±.015 (0,381 mm) | 3 PLACE DECIMAL ±.005 (0,127 mm) | ANGLES ± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL: SEE NOTES

REFERENCE:

DRAWN: CLEMENT	DATE: 13-Mar-14	TITLE: SMA CRIMP PLUG TO SMA BULKHEAD CRIMP JACK USING RG 316/U COAXIAL CABLE, VARIOUS LENGTHS
ENGINEER: CLEMENT	DATE: 13-Mar-14	
APPROVED: B.C. GLEISSNER	DATE: 26-Mar-14	
CAD FILE	DWG SIZE: B	DRAWING NO.: 135110-01-XX.XX REV: B

Amphenol Connex

SCALE: 2.5:1 SHEET 2 OF 2

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Amphenol:

GTC08-32-17SX-025-LC M39012/56-3028 97-14S-6P D38999/20WE6PN M85049/52S18W M85049/79-09W02 RJHSE7367 RTS010N4S03 1115-6088 97-3102A-10SL-3P(958) C016 20G003 200 12 CF-198136-000 GTS08-32-17SY-025 L77SDC37SVFC309 M85049/7915W03 112589 SLPIPB70BSB2EH 122373 AD-NPMCXJ-2 MA1LAE1200-KIT PTIH-8-4P EP-8-11P MRDAH03M15000 MS3102A-14S-2SY 9760-24P 034-1046 62GB56TG1404PN 97-4106A-18-12P M85049/1819W03 MUSB2K15015BP