
Product sheet
Automation technology

Product	Female angled connector moulded, screw version, M8 x 1, LED	Pole	3
Area	M8 connectors serie 718	Article number	79 3404 42 03


illustration



scale drawing



Contact Arrangement



1 braun
3 blau
4 schwarz

Technical data

Common values

Connector Design	Female angled cable connector
Connector locking system	Screw-locking
Termination	crimp, overmoulded on cable
Wire gauge (mm)	0,25 mm²
Wire gauge (AWG)	24
Upper temperature	+85 °C
Lower temperature	-25 °C

Electrical values

Rated voltage	60 V
Rated impulse voltage	800 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
Degree of protection	IP 67
Mechanical operation	>100 mating cycles

Material

Material of contact	CuZn (brass)
Contact plating	Au (gold)
Material of contact body	PUR
Material of housing	PUR

Cable data

material housing	PVC
insulation single lead	PVC
single lead structure	32 x 0,1
cable sheath Ø	4.5
conductor resistance	79,5Ω/Km

Contacts 3, cable: 2 m, 3 x 0,25 PVC, Male angled connector moulded, screw version, M8 x 1, LED

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Franz Binder:

09-9749-20-03 99-0491-12-12 86 6919 0002 00703 99-0430-27-04 99-9115-00-05 99-0429-314-04
99-3376-100-04 99-4929-00-08 04 0722 000 09-0981-00-04 09-3481-679-08 79 5001 20 04 99-0401-10-02
99-0609-00-04 99-9475-100-07 09 3463 00 06 09-3432-500-04 09-3442-92-05 79-3468-52-06
99 0975 102 03 99-0072-100-02 99-3400-00-03 09-0498-00-24 14402780 99-0096-100-05 99-4905-00-03
09 0137 70 04 09-0315-00-05 09-3105-86-03 09-3491-90-12