
Pneumatic shock absorber
YSRW-8-14

Part number: 191194





General operating condition

Data sheet

Feature	Value
Size	8
Stroke	14 mm
Cushioning	Self-adjusting Soft characteristic curve
Mounting position	Any
Position sensing	None
Symbol	00991495
Max. impact velocity	3 m/s
Reset time at room temperature	0.2 s
Reset time at min. ambient temperature	1 s
Mode of operation	Pushing Single-acting
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Ambient temperature	-10 °C ... 80 °C
Cushioning length	14 mm
Max. stop force	500 N
Max. energy absorption per stroke	4 J
Max. energy absorption per hour	21000 J
Max. residual energy	0.02 J
Resetting force	2.5 N
Min. insertion force	18 N
Product weight	34 g
Load range	10 kg
Type of mounting	With lock nut
Note on materials	RoHS-compliant
Seals material	NBR
Housing material	High-alloy steel
Piston rod material	High-alloy steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

SPTE-V1R-Q3-V-2.5K CRVZS-0.4 PUN-H-4X0,75-TBL QSLL-1/4-4 QSLV-G1/4-6 QSML-3
DSBC-32-40-D3-PPVA-N3 DSBC-50-20-D3-PPSA-N3 NPQP-LQ-R18-Q8-FD-P10 QH-1 1/2 VBQF-U-G14-E
DSBC-63-320-D3-PPVA-N3 DSNU-12-60-P-A NPQH-T-G38-Q8-P10 NPQP-Y-Q6-E-FD-P10 QS-1/2-16
VABM-L1-18W-G38-8-G NPQP-LQ-R18-Q4-FD-P10 SNC-63 N-1/8-P-6 NPQP-Y-R12-Q12-FD QSS-8-F
DFM-63-100-P-A-KF DSBC-32-50-D3-PPVA-N3 DSBC-80-250-D3-PPSA-N3 QSML-6 MSFW-110-50/60-DS
NPQP-D-Q4-S8-FD-P10 DSBC-80-320-D3-PPVA-N3 NPQP-L-Q10-E-FD-P10