
NPN Epitaxial Silicon Transistor

KSD1588



1. Base
2. Collector
3. Emitter

TO−220 Fullpack
CASE 221AT

Low Frequency Power Amplifier

- Low Speed Switching
- This is a Pb−Free Device

ABSOLUTE MAXIMUM RATINGS


(T_C = 25°C unless otherwise noted.)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector−Base Voltage	100	V
V_{CEO}	Collector−Emitter Voltage	60	V
V_{EBO}	Emitter−Base Voltage	7	V
I_C	Collector Current (DC)	7	A
I_{CP}	Collector Current (Pulse) (Note 1)	15	A
I_B	Base Current	3.5	A
P_C	Collector Dissipation (T_A = 25°C)	2	W
	Collector Dissipation (T_C = 25°C)	30	W
T_J	Junction Temperature	150	°C
T_{STG}	Storage Temperature	−55 ~ 150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. PW ≤ 300 μs, Duty Cycle ≤ 10%.

MARKING DIAGRAM



D1588 = Specific Device Code
Y = h_{FE} Grade
A = Site Code
YWW = Date Code (Year & Week)
ZZ = Assembly Lot Code

ORDERING INFORMATION

Device	Package	Shipping
KSD1588YTU	TO−220 Fullpack (Pb−Free)	1,000 Units / Tube

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted.)

Symbol	Parameter	Test Conditions	Min	Max	Unit
I_{CBO}	Collector Cut−off Current	V_{CB} = 80 V, I_E = 0	−	10	μA
I_{EBO}	Emitter Cut−off Current	V_{EB} = 5 V, I_C = 0	−	10	μA
h_{FE1} h_{FE2}	DC Current Gain (Note 2)	V_{CE} = 1 V, I_C = 3 A V_{CE} = 1 V, I_C = 5 A	40 20	200 −	
V_{CE}(sat)	Collector−Emitter Saturation Voltage (Note 2)	I_C = 5 A, I_B = 0.5 A	−	0.5	V
V_{BE}(sat)	Base−Emitter Saturation Voltage (Note 2)	I_C = 5 A, I_B = 0.5 A	−	1.5	V

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. Pulse Test: PW ≤ 350 μs, Duty Cycle ≤ 2%.

h_{FE1} Classification

Classification	R	O	Y
h_{FE1}	40 ~ 80	80 ~ 120	100 ~ 200

© Semiconductor Components Industries, LLC, 2000

TYPICAL CHARACTERISTICS




Figure 1. Static Characteristic




Figure 2. DC Current Gain




Figure 3. Base−Emitter Saturation Voltage and Collector−Emitter Saturation Voltage




Figure 4. Safe Operating Area




Figure 5. Derating Curve Safe Operating Area






Figure 6. Power Derating


TO−220 Fullpack, 3−Lead / TO−220F−3SG
CASE 221AT
ISSUE B


DATE 19 JAN 2021



Scale 1:1







DIM	MILLIMITERS		
	MIN	NOM	MAX
A	4.50	4.70	4.90
A1	2.56	2.76	2.96
A2	2.34	2.54	2.74
b	0.70	0.80	0.90
b2	~	~	1.47
c	0.45	0.50	0.60
D	15.67	15.87	16.07
D1	15.60	15.80	16.00
E	9.96	10.16	10.36
e	2.34	2.54	2.74
F	~	0.84	~
H1	6.48	6.68	6.88
L	12.78	12.98	13.18
L1	3.03	3.23	3.43
ø P	2.98	3.18	3.38
ø P1	~	1.00	~
Q	3.20	3.30	3.40

NOTES:
A. DIMENSION AND TOLERANCE AS ASME Y14.5-2009
B. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR PROTRUCSIONS.
C. OPTION 1 - WITH SUPPORT PIN HOLE
OPTION 2 - NO SUPPORT PIN HOLE

DOCUMENT NUMBER:	**98AON67439E**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**TO−220 FULLPACK, 3−LEAD / TO−220F−3SG**	**PAGE 1 OF 1**

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Fairchild Semiconductor:

FDS2672 FQPF3N80C FSL126MR ISL9V3040P3 MM74HC139N 1N4148TA FDB8030L FDP12N60NZ FDS6990A FDS8928A HLMP0504 ISL9V3040S3ST KA278R12CYDTU 74VHC573MX H11L1M MMBT3640 RFP12N10L SI9435DY FCP190N60E FDS6375 FQP6N90C KST42MTF SI9936DY 1N4148 74ACQ573SCX DM7407MX