
SPECIFICATIONS

(RoHS Compliant)

Model Number: CR6025-UXD24BPL Version: 00

Part Number: 17002017A May 15, 2023

Mechanical Drawing:



Motor:

Nominal Voltage	= 24vdc
Operating Voltage Range	= 21.6– 26.4 vdc
Nominal Running Current	= 0.21amps
Max. Locked Rotor Current	= 0.5 amps
Running Power	= 5.04watts
Average Speed	= 6000 RPM
Bearings	= Ball
Air Flow	= 29.8CFM
Acoustic	= 54 dBA
Weight	= 70g

Construction:

Venturi: Plastic, Black, UL 94V-0
Propeller: Plastic, Black, UL 94V-0

Life Expectancy:

This fan is designed for continuous duty life of 45,000 hours at 70°C.

Additional Features:

Brushless DC Motor
Automatic Restart Capability
Electronic Locked Rotor Protection
Polarity Protected

Operating Temperature:	-10°C to 70°C
Storage Temperature:	-40°C to 85°C


Agencies:

UL, CE

Termination:

250±10mm , 24AWG UL1007 Leadwires
Red = Power(+)
Black = Return(-)

PQ Curve:


m³/Hr
0
9
17
26
35
43
52
61
Static Pressure (in H2O)
0.40
0.35
0.30
0.25
0.20
0.15
0.10
0.05
0.00
100
87
75
62
50
37
25
12
0
Pa
0
5
10
15
20
25
30
35
CFM

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Comair Rotron:

19028868A 19030616A 19030622A 19032105A 19032183A 19039671A GL24B7-E2 19039031A 032740
17002001A 19028885A 19039299A 19039306A 17001219A 476042 GDA1238-48BB 19030389A
19039646A 17002016A MD24B5-E2 19039030A 031176 19031092A MA2B3 19031842A 031081
17001178A 17002087A 19028933A CLE2L2 19020188A 032620 032772 039824