Quick Links
Cross reference
RoHS/LF P/N Search
Industry Standards
Alphabetical List

Documentation
3D model search
Customer drawing search
Multi Selection Search
Search by category

10117184-09B10EHLF

10117184-09B10EHLF - FPC/FFC : SFGL Series, 9 Pos, Bottom Side Contact, Side Entry Surface Mount ZIF Connector, 0.2 mm (0.008 in.), Halogen and Lead Free Type, Back side flip

ACTIVE

RoHS Compliant

Distributor Stock

Print Datasheet

FCI Brings You More
Contact our sales/technical support
Sample request



Customer drawing

Product Environmental Compliance Report

Specifications | Download document

General | Electrical | Mechanical | Physical | Environmental | Other Features

General	
Cable Lock	Yes
Contact location	Bottom
Number of contacts	9
Orientation	Right Angle
Product Series	SFGL
Electrical	
Withstanding Voltage	200V AC for 1 minute
Current rating	0.4A AC/DC
Resistance (Contact)	50 milli ohms max
Resistance (Insulation)	50 M-ohms min.
Voltage rating	50V AC/DC
Mechanical	
Durability (Mating cycles)	20 Cycles
Vibration per IEC Pub 68-2-6	No discontinuity > 1 µ second
Physical	
Material (Contact)	Phosphor Bronze, Gold Flash Plated
Material (Housing)	Glass Reinforced LCP, UL94 V-0
Material (Slider)	Glass Reinforced PPS, UL94 V-0
Temperature (Operating - range)	-55°C to +85°C
Environmental	
Salt Spray per IEC Pub 68-2-11	50 milli ohms max
Damp Heat per IEC Pub 68-2-3	50 milli ohms max
Themal Shock per IEC Pub 68-2-14	50 milli ohms max
Other Features	
Packaging (Type)	Embossed Tape on Reel

Disclaimer : The information above is for reference only. For more technical details, refer to product specification and application specification.

Quick Links
Cross reference
RoHS/LF P/N Search
Industry Standards
Alphabetical List

Documentation
3D model search
Customer drawing search
Multi Selection Search
Search by category

Start > Search=10117184-09B10EHLF* > 10117184-09B10EHLF

10117184-09B10EHLF

10117184-09B10EHLF - FPC/FFC : SFGL Series, 9 Pos, Bottom Side Contact, Side Entry Surface Mount ZIF Connector, 0.2 mm (0.008 in.), Halogen and Lead Free Type, Back side flip

ACTIVE

RoHS Compliant

Distributor Stock

Print Datasheet

FCI Brings You More
Contact our sales/technical support
Sample request



Customer drawing

Product Environmental Compliance Report

Specifications | Download document

General | Electrical | Mechanical | Physical | Environmental | Other Features

General	
Cable Lock	Yes
Contact location	Bottom
Number of contacts	9
Orientation	Right Angle

Downloaded from Arrow.com.

Product Series	SFGL
Electrical	
Withstanding Voltage	200V AC for 1 minute
Current rating	0.4A AC/DC
Resistance (Contact)	50 milli ohms max
Resistance (Insulation)	50 M-ohms min.
Voltage rating	50V AC/DC
Mechanical	
Durability (Mating cycles)	20 Cycles
Vibration per IEC Pub 68-2-6	No discontinuity > 1 µ second
Physical	
Material (Contact)	Phosphor Bronze, Gold Flash Plated
Material (Housing)	Glass Reinforced LCP, UL94 V-0
Material (Slider)	Glass Reinforced PPS, UL94 V-0
Temperature (Operating - range)	-55°C to +85°C
Environmental	
Salt Spray per IEC Pub 68-2-11	50 milli ohms max
Damp Heat per IEC Pub 68-2-3	50 milli ohms max
Themal Shock per IEC Pub 68-2-14	50 milli ohms max
Other Features	
Packaging (Type)	Embossed Tape on Reel

Disclaimer : The information above is for reference only. For more technical details, refer to product specification and application specification.

© AFCI 2016 All Rights Reserved | Privacy Policy | Terms of Use | Terms and Conditions

Downloaded from Arrow.com.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Amphenol:

54202-G0805CLF 68000-236HLF 91614-403ALF CD15S13E4RV09LF 70430-164LF 86130202123355E1LF LD15P33E4GV00LF 86093967896755LF DCMF37P 69192-408HLF 86093968191755E3LF 863013A LD25S33E4GV00LF 70218-1116LF 86093968813H45V1LF 95157-140LF DAPO15S365TLF RJSBE5080C2 67996-204HLF 68001-108HLF 68001-200HLF 54202-S08-07LF 65781-158 68002116HLF 76384-316LF RJE061661210 70234-112LF 86093488314745V1LF D15P13A6RV12LF DEM09P032N