


REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A1	N/A		图框升级整理图面	2024.07.31	阿 树









■SPECIFICATIONS
- Voltage rating:600V AC/DC
- Current rating:9A AC/DC
- Withstanding Voltage:1500V AC/minute
- Temperature range:−45°C+125°C
- Insulation resistance:≥1000MΩ
- Contact resistance:≤10mΩ


PART NO.:

X9357 W V−04−LP SW
① ② ③ ④ ⑤ ⑥

① Series No
② Category:W−Wager
③ Welding Board Angle:V−Straight 180°
④ Row No.Pin No:XX−02~12P
⑤ Material:LP−LCP 94V−0
⑥ Plating:SW−Matte Tin







PCB Layout

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
02	4.20	9.60	08	29.40	34.80
03	8.40	13.80	09	33.60	39.00
04	12.60	18.00	10	37.80	43.20
05	16.80	22.20	11	42.00	47.40
06	21.00	26.40	12	46.20	51.60
07	25.20	30.60	/		

X9357WV−04−LPSW	LCP	Brass	Matte Tin	X9357HM
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Housing

ANGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	

XKB INDUSTRIAL PRECISION CO.,LIMITED

DESIGN	阿 树	VIEW:	MODEL TYPE: 4.20 mm Crimp Style Connectors
CHECKED		UNIT: mm/in	PART NO.: X9357WV−04−LPSW
APPROVED		SIZE: A4	DWG NO.: X−X9357WV−04−LPSW

SCALE	PAGE	REVISION
N/A	1/1	A1