Push-in Y-fitting
QSY-3/8-10

Part number: 153145

FESTO



General operating condition

Data sheet

Feature	Value
Size	Standard
Nominal width	7.4 mm
Type of seal on screwed plug	Coating
Mounting position	Any
Design	Y-shape
Pack size	10
Structural design	Push-pull principle
Operating pressure for entire temperature range	-0.095 MPa ... 0.6 MPa
Operating pressure for entire temperature range	-0.95 bar ... 6 bar
Operating pressure for entire temperature range	-13.775 psi ... 87 psi
Temperature-dependent operating pressure	-0.095 MPa ... 1.4 MPa
Temperature-dependent operating pressure	-0.95 bar ... 14 bar
Temperature-dependent operating pressure	-13.775 psi ... 203 psi
Information on operating pressure	Water: max. 0.6 MPa at max. 50 °C
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-] Water (liquid, ice-free)
Information on operating and pilot media	Operation with oil lubrication possible
Corrosion resistance class (CRC)	1 - Low corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	-10 °C ... 80 °C
Nominal tightening torque	15.5 Nm
Tolerance for nominal tightening torque	± 20%
Product weight	43 g
No. of outlets	2
No. of supply lines	1
Type of mounting	External hexagon, AF 17
Pneumatic connection 1	External thread R3/8
Pneumatic connection 2	for pneumatic tubing outside diameter 10 mm
Releasing ring color	Blue
Material of screwed plug	Brass, nickel-plated
Note on materials	RoHS-compliant
Housing material	PBT
Releasing ring material	POM
Material of tubing seal	NBR
Material of tube retaining claw	High-alloy stainless steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

QSML-6 QSS-8-F QSY-6H-4 VBQF-U-G14-E 153307 QSF-1/4-8-B VABM-B10-25S-G38-6-P3 153367 NPQH-T-Q14-E-P10 SGS-M10X1,25 NPQP-L-Q10-E-FD-P10 NPQP-LQ-R18-Q4-FD-P10 NPQP-LQ-R18-Q8-FD-P10 NPQP-Y-Q6-E-FD-P10 NPQP-Y-R12-Q12-FD QS-10H-6 VABM-B10-25S-G38-10 NPQP-D-Q4-S8-FD-P10 QS-1/2-16 QSF-3/8-8-B 153031 CRVZS-0.4 DSBC-80-20-D3-PPSA-N3 153269 HGL-1/8-QS-6 SASC-P4-A-M8-A NPQP-T-Q8-E-FD-P10 QSLL-G1/2-12 153151 QS-1/8-8-I